

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-399-40

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Dry hole</b>	7. Unit Agreement Name
2. Name of Operator <b>Chambers &amp; Kennedy</b>	8. Farm or Lease Name <b>Northwest Caprock Unit</b>
3. Address of Operator <b>607 Midland Nat'l. Bk. Bldg., Midland, Texas 79701</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>C</b> , <b>660</b> FEET FROM THE <b>N</b> LINE AND <b>1980</b> FEET FROM THE <b>W</b> LINE, SECTION <b>8</b> TOWNSHIP <b>12N</b> RANGE <b>32E</b> NMPM.	10. Field and Pool, or Wildcat <b>Wildcat</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4405' CR.</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER **Re-entry** ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Re-entered well drilled by Murphy Corp. in 1961, in an attempt to drill out cement plugs and test Morrow zones, from 10814' to 10860' & 10525 to 10575'. Drilled cement plugs in 13-3/8" surface casing & 9-5/8" casing and reached a total depth of 2054' inside 9-5/8" casing. On 12/16/69, recovered junk from hole at 2054' & were unable to drill below 2054'. Will plug and abandon in the following manner: load hole with 9.5# mud. Spot a 30 sack cement plug from 620' & a 30 sack cement plug from 360' & a 10 sack cement plug at surface. Re-install permanent marker (4" pipe - 4' above ground) & clear location & level pits. (Top of 9-5/8" casing is at 594'. Bottom of 13-3/8" casing is at 350'.

Note - Verbal permission granted 12/17/69 by Mr. John Runyan, New Mexico Oil Conservation Commission.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <b>G. C. Thompson</b>	TITLE <b>Manager of Production</b>	DATE <b>Dec. 18, 1969</b>
APPROVED BY <b>[Signature]</b>	TITLE <b>SUPERVISOR DISTRICT</b>	DATE <b>DEC 23 1969</b>
CONDITIONS OF APPROVAL, IF ANY:		