

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) See Below	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Tatum, New Mexico
(Place)

October 4, 1957
(Date)

Gentlemen:

East Caprock Salt Water Disposal

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation Well No. 1 in "J" (Company or Operator)
NE 1/4 SE 1/4 of Sec. 11, T. 12-S, R. 32-E, NMPM., East Caprock Pool
(40-acre Subdivision)
Lea County County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Change name of Well to: East Caprock Salt Water Disposal Well #1.
Formerly Carried as: H.C. Pacey "A" #2 (East Caprock Field)

Well Plugged and abandoned on 8-28-52 - Well Picked up on 8-27-56
to Convert to a Salt Water Disposal Well for east Caprock Devonian Field.
Well Has been used as a Salt Water Well since that date.

Intensions are to drill Baker Model "D" Production Packer @ 1250' & Baker Model "K"
Cast Iron Bridge Plug @ 1610' & Drill Cement Plug in 8-5/8" Csg. From 3563' to 3615' and
in Open hole from 3615' to 3665', Wash out to 5050' & Set Cement Plug in 7-7/8" Open Hole
from 4950'-5050' & Acidize W/2500 Gallons Acid.

11,283' TD 1608' PEB
13-3/8" Csg. Set @ 296' W/225 Sx. Cement
8-5/8" Csg. Set @ 3615' W/1500 Sx. Cement.

Approved _____, 19____
Except as follows:

Amerada Petroleum Corporation

Company or Operator

By _____

Position: Foreman

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By _____

Title _____

Name: Amerada Petroleum Corporation

Address: Roswell Star Route - Tatum, New Mexico

