

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered desirable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) See below	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Tatum, New Mexico

August 27, 1956

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the H. C. Posey "A"

Amerada Petroleum Corporation

(Company or Operator)

Well No. 2 in "I"

NE 1/4 SE 1/4 of Sec. 11, T. 12-S, R. 32-E, NMPM, East Caprock Pool  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

11,283' TD, Top cement plug in 8-5/8" Casing @ 3563'

Well plugged and abandoned on 8-28-52.

13-3/8" Casing set @ 296' w/ 225 sx. cement

8-5/8" Casing set @ 3615' w/ 1500 sx. cement

Casing was not recovered.

The following proposal of work is planned to determine if this well is suitable for a salt water disposal well for the East Caprock field.

Plan to displace mud from 8-5/8" Casing and set Baker Cast Iron Bridge Plug on wire line @ 1610' and dump 2 sx. cement on top plug. Perforate 8-5/8" Casing from 1300' to 1450' with 4 bullets per foot. Run 3-1/2" Tubing, Packer and Hold-down and swab casing perforations from 1300' - 1450'. Will pump water into formation from 1300' - 1450'. If zone will not take sufficient amount of water suitable for injection, plan to acidize with 1,000 gallons mud acid and test.

Approved SEP 5 1956, 19.

Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By C. M. Linder

Title Engineer District I

Amerada Petroleum Corporation

(Company or Operator)

By J. M. Linder

Position Foreman

Send Communications regarding well to:

Name Amerada Petroleum Corporation

Address Roswell Star Rt., Tatum, New Mexico