

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**Santa Fe, New Mexico**

**MISCELLANEOUS REPORTS ON WELLS**

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test casing shut-off, results of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<b>X</b>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 27, 1953

(Date)

Tatum, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation  
 (Company or Operator)

State EC\*G\*

(Lease)

Rowan Drilling Company, Inc.  
 (Contractor)

Well No. 1 in the NE  $\frac{1}{4}$  SE  $\frac{1}{4}$  of Sec. 10

T. 12-S, R. 32-E, NMPM., East Caprock - Devonian Pool, Lea County.

The Dates of this work were as follows: June 26, 1953

Notice of intention to do the work (was) (~~not~~) submitted on Form C-102 on June 25, 1953  
 (Cross out incorrect words)

and approval of the proposed plan (was) (~~not~~) obtained.

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

**10,834' Total Depth. Lins. Finished drilling 7-7/8" hole to 10,834' @ 1:15 PM, on 6/23/53. Ran Schlumberger surveys. Ran Drill Stem Test #8 from 10,509' to 10,834' with no show of gas, oil or formation water. Filled hole with heavy drilling mud and spotted a 35 sack cement plug from 9950' to 10,065'; from 9300' to 9400' spotted a 30 sack cement plug; from 8600' to 8715' spotted a 35 sack cement plug and from 3553' to 3655' spotted a 35 sack cement plug. Ran Dia-log free-point indicator on 8-5/8" casing and found free point @ 629' - ran Dia-log casing cutter and cut 8-5/8" casing off @ 604'. Pulled a total of 16 jts of 8-5/8" OD casing for 591'. Filled hole with drilling mud and spotted a 10 sack cement plug from 285' to 297'; spotted a 10 sack cement plug in top of 13-3/8" OD casing from surface to 10' down. A piece of 4" line pipe placed in top cement plug and extends 5' above ground level to serve as a marker. Well plugged and abandoned on June 26, 1953.**

Witnessed by I. W. Wiseman  
 (Name)

Amerada Petroleum Corporation  
 (Company)

Foreman  
 (Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name, [Signature]

Position, Assistant District Superintendent

Representing Amerada Petroleum Corporation

Roswell Star Route Tatum, New Mexico  
 Address

[Signature]  
 (Title)

(Date)