

Santa Fe, New Mexico

**T
12
S**

AREA 640 ACRES
LOCATE WELL CORRECTLY

State EC^uCⁿ
(Lease)

OIL SANDS OR ZONES

IMPORTANT WATER SANDS

CASING RECORD

MUDDING AND CEMENTING RECORD

RECORD OF PRODUCTION AND STIMULATION

Depth Cleaned Out.....

CORD OF DRILL-STEM AND SPECIAL TI

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 11228 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Feb. 2, 1953, 19
OIL WELL: The production during the first 24 hours was 1089.60 barrels of liquid of which 98.41 % was oil; % was emulsion; 1.28 % water; and .31 % was sediment. A.P.I. Gravity 44.1 corrected -
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy		T. Devonian	10955	T. Ojo Alamo	
T. Salt	1524	T. Silurian		T. Kirtland-Fruitland	
B. Salt	2143	T. Montoya		T. Farmington	
T. Yates	2270	T. Simpson		T. Pictured Cliffs	
T. 7 Rivers		T. McKee		T. Menefee	
T. Queen		T. Ellenburger		T. Point Lookout	
T. Grayburg		T. Gr. Wash		T. Mancos	
T. San Andres	3552	T. Granite		T. Dakota	
T. Glorieta		T.		T. Morrison	
T. Drinkard		T.		T. Penn	
T. Tubbs		T.		T.	
T. Abo	7170	T.		T.	
T. Wolfcamp	8210	T.		T.	
T. Pennsylvanian	8480	T.		T.	
T. Miss.	10360				

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	6	6	Cellar				
6	300	294	Sand & Caliche				
300	1460	1160	Shale and Sand				
1460	1520	60	Anhydrite and Shale				
1520	2200	680	Salt, Anhydrite and Shale				
2200	2280	80	Shale, Anhydrite, Sand & Salt				
2280	3570	1290	Shale, Anhydrite, Sand & Salt				
3570	4320	750	Dolomite and Anhydrite				
4320	4780	460	Limestone				
4780	7170	2390	Dolomite, Anhydrite, Sand Stringers				
7170	7800	630	Shale, Dolomite and Anhydrite				
7800	8140	340	Dolomite and Anhydrite				
8140	8250	110	Chert, Dolomite and Anhydrite				
8250	8360	110	Dolomite				
8360	8525	330	Chert, Dolomite and Limestone				
8525	8855	165	Limestone				
8855	10300	1445	Sand, Chert, Shale and Limestone				
10300	10920	620	Shale, Limestone W/Trace of Chert				
10925	10955	30	Sand & Limestone				
10955	11228	273	Dolomite W/Chert Stringers				
	11228		Total Depth -				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

February 23, 1953

(Date)

Company or Operator Amerada Petroleum Corporation

Address Drawer D, Monument, New Mexico

Name

H.C. Carpp

Position or Title District Superintendent