

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 22, 1953  
(Date)

Tatum, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation  
(Company or Operator)

State ES #7  
(Lease)

Rewan Drilling Company, Inc.  
(Contractor)

Well No. 1 in the SW 1/4 SW 1/4 of Sec. 11

T. 12-S, R. 32-E, NMPM., East Caprock - Devonian Pool, Lea County.

The Dates of this work were as follows: April 21, 1953

Notice of intention to do the work ~~work~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan ~~work~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,302' Total Depth. Lins. Finished drilling 7-7/8" hole at 1:55 PM, 4/17/53, to depth of 11,302'. Ran Schlumberger surveys. Ran Drill Stem Test from 11,260' to 11,302' - 2 hour and 40 minute test. Flowed 233.92 bbls oil - 1.42 bbls BS & G-water in two hours. Gas Volume 63,160 CFPS. GOR - 22. Ran a total of 315 joints 5-1/2" OD casing set @ 11,270' and cemented with 700 sacks cement. Pumped plug to 11,182' @ 10:55 PM, 4/19/53. Max. Pump Pressure - 1800#. Ran temperature survey and found top of cement outside of 5-1/2" casing @ 8134' or 65.2% fill. After W.O.G. for 24 hours tested 5-1/2" OD casing with 1800# for 1/2 hour - no pressure drop. Drilled cement from 11,182' to 11,270' and washed to 11,302'. Tested 5-1/2" OD casing with 1800# for 1/2 hour - no pressure drop. Continued with completion operations.

Witnessed by R. J. Brakey Amerada Petroleum Corporation Farm Boss  
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: R. V. Thompson

Position: Assistant District Superintendent

Representing: Amerada Petroleum Corporation

Address: Roswell Star Route Tatum, New Mexico

Ray Yankovich  
Oil & Gas Inspector  
(Title)

APR 24 1953  
(Date)

Handwritten text, mostly illegible due to extreme fading and bleed-through. Some fragments are visible, such as "the" and "and".

Handwritten text at the bottom left, possibly a signature or date, mostly illegible.

Handwritten text at the bottom right, possibly a signature or date, mostly illegible.