			Supersedes Old
DISTRIBUTION			C-102 and C-103
SANTA FE	NEW MEXICO O	NEW MEXICO OIL CONSERVATION COMMISSION	
FILE			
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State Fee X
OPERATOR .		•	5. State Oil & Gas Lease No.
OFERATOR			
	CHARDY MOTICES AND DEDO	DTS ON WELLS	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)			
	**APPLICATION FOR PERMIT (FORM C-10	1) FOR SUCH PROPOSICION	7. Unit Agreement Name
l. OIL GAS			·
WELL WEL	OTHER- Salt wate:	r disposai	8. Farm or Lease Name
2. Name of Operator			East Caprock S.W.D.
Amerada Hess Corporation			9. Well No.
3. Address of Operator			2
Drawer D, Monument, New Mexico 88265			10. Field and Pool, or Wildcat
4. Location of Well			
UNIT LETTER B		orth Line and 2310 FEET FR	ow Francisco
Tue East	INE, SECTION 14 TOWNSHIP	12-S RANGE 32-E NMI	··· (
, nc			
	,,,,,,,,,,	nw whether DF, RT, GR, etc.)	12. County
	435	4' DF	Lea
PERFORM REMEDIAL WORK TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	EUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, included the for holes and IPC. Ran 4-1, 210'. Ran McCullough csg. 1/2" csg. to 11,040'. Ran II, 134'. Displaced annulus wand resumed disposing water	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or of work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or of work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or of work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or of work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or of work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
17. Describe Proposed or of work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
To Describe Proposed or work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
To Describe Proposed or work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
To Describe Proposed or work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
To Describe Proposed or work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water
To Describe Proposed or work) SEE RULE 1103 February 1977: Pulled 3-1/2" from inside 5- 3500' to 11,20 402 jts. 3-1/2 mixed with 55	CUE tbg. & inspected same 1/2" csg. fr. 8812' to 130'. Ran gauge ring in 50' IPC tbg. Set pkr. at 2 gal. corrosion inhibitor	ertinent details, and give pertinent dates, includes for holes and IPC. Ran 4-1, 210'. Ran McCullough csg.	5/8" bit and cleaned scale inspection log from Baker lok-set pkr. on with 131 bbls. water

Sexton Sexton

CONDITIONS OF APPROVAL, IF ANY:

3-25-77

MAR 28 1977

REDEIMED

1..... 2 (1977

the second of the first th