

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO
Tatum, New Mexico
(Place)
April 15, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation Bula Chestwood
(Company or Operator)
Well No. 1 in 1
(Unit)
C-NW 1/4 SW 1/4 of Sec. 14, T. 12-S, R. 32-E, NMPM, Undesignated Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

3009' Total Depth. Sand. 5-1/2" OD casing was set @ 2994' and open hole from 2994' to 3009' treated with 20,000 gallons free-oil with 20,000 lbs. sand. Total of lead and treatment oil used was 781 bbls. Swabbed well for 24 hrs and recovered 425 bbls of lead/treatment oil. Installed pumping unit and ran sub-surface tubing pump set @ 2956'. Well tested on pump for 14 day period - production diminished to rate of 1.15 bbls lead oil and 2.78 bbls water for 6 hour period - at end of pumping test period lacked 326 bbls. lead oil of recovering total lead oil injected in well bore.

It is our intention to plug and abandon this well. It is proposed to spot 6 sz cement plug (2959' to 3009'), 4 sz cement plug (1920' to 1952'), 25 sz cement plug (1460' to 1481') and 10 sz plug in top of 8-5/8" OD surface casing. Before spotting plugs as above - attempt will be made to pull 5-1/2" OD casing after cutting @ approximately 1920'. (Top of cement outside of 5 1/2" casing @ 1931') Hole will be filled with heavy drilling mud between plugs - required marker will be placed in surface plug.

Approved
Except as follows:

Amerada Petroleum Corporation
(Company or Operator)
By

Position: Assistant District Superintendent
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION
By
Title

Name: Amerada Petroleum Corporation
Address: Beaswell Star Route Tatum, New Mexico