

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

March 21, 1955
(Date)

Tatum, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)

Bula Chestwood
(Lease)

McQueen and Stout Drilling Contractors
(Contractor)

Well No. 1 in the NW 1/4 SW 1/4 of Sec. 14

T. 12-S, R. 32-E, NMPM, (Indesignated) Pool, Lea County.

The Dates of this work were as follows: March 19, 1955

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3009' Total Depth. Sand. Finished drilling 7-7/8" hole to 2975' @ 10:30 AM on 3-16-55. Cored 7-1/4" hole from 2975' to 3009'. Finished coring 7-1/4" hole @ 4:00 AM on 3-17-55. Ran Schlumberger surveys. Ran 72 jts of 5-1/2" OD casing set @ 2994' and cemented with 200 sacks cement. Plug down to 2949' @ 4:25 AM on 3-18-55. Max. pump pressure - 1200#. Ran temperature survey and found top of cement outside of 5-1/2" OD casing @ 1931' or 85.1% fill. After W.O.C. for 24 hours tested 5-1/2" OD casing before drilling cement with 1200# for 1/2 hour - no pressure drop. Drilled cement from 2949' to 2994' and tested 5-1/2" OD casing with 1200# for 1/2 hour - no pressure drop. Continued with completion operations.

Witnessed by R. Q. Swanson
(Name)

Amerada Petroleum Corporation
(Company)

Farm Boss
(Title)

Approved: OIL CONSERVATION COMMISSION

J. G. Stanley
(Name)
(Title) (Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: R. Q. Swanson

Position: Assistant District Superintendent

Representing: Amerada Petroleum Corporation

Address: Roswell Star Route Tatum, New Mexico

