

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES DEC 27 2 53 PM '63

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

December 27, 1963  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation State EC "A" Well No. 1 in C  
(Company or Operator) (Unit)  
NE 1/4 NW 1/4 of Sec. 14, T. 12S, R. 32E, NMPM, East Caprock Dev. Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Pull rodup pump and tubing. Squeeze Devonian zone 5-1/2" casing perfs. from 11,260' to 11,270' with 150 sacks sls-set cement. Drill out to 11,258'. Perforate 5-1/2" casing from 11,249' to 11,254' with 2 shots per foot. Acidize perfs. with 500 gals. 15% reg. acid. Test. If work is not successful, run cement bond log to check cement behind 5-1/2" casing from 8200' to 9200'. If log shows poor cement job, perforate with 2 shots from 8220' to 8222' and squeeze with 100 sacks cement. Set cast iron bridge plug at 8830' with 1 sack cement on top of plug. Perforate 5-1/2" casing from 8710' to 8720', 8740' to 8766' and 8774' to 8790' with 2 shots per foot. Acidize perfs. with 2000 gals. 15% reg. acid. Recomplete as a producer from Pennsylvanian zone.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

Amerada Petroleum Corporation  
Company or Operator

By.....

Position.....

Send Communications regarding well to:

Name..... Amerada Petroleum Corporation

Address..... Box 668 - Hobbs, New Mexico

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92