

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Tatum, New Mexico
(Place)

April 18, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation
(Company or Operator)

Kila Speed

Well No. 1 in M (Unit)

6/34 1/4 34/ 1/4 of Sec. 15, T. 12-S, R. 32-E, NMPM, North Sparrow-Queen (Extension) b1
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

3038' Total Depth. Sand. 5-1/2" OD casing was set @ 3018' and 4-3/4" hole drilled to 3038'. Open hole from 3018' to 3038' was treated by Halliburton sand-oil treatment with 20,000 gallons frac-oil and 20,000 lbs. sand. Total of load/treatment oil used was 712 bbls. After treatment well flowed on treatment pressure and swabbed a total of 266 bbls lead oil. Ran Lane-Wells Tracer Fluid Survey and injected 130 bbls lead oil in casing during survey. After well swabbed to depletion had recovered 136 bbls lead oil.

It is proposed that the well be plugged and abandoned. Attempt will be made to salvage 5-1/2" OD casing from surface to approximately 1700'. (Top of cement outside of 5-1/2" OD casing @ 1706') An 8 sack cement plug will then be spotted from 2972' to 3038', a 25 sack cement plug from 1400' to 1481' and a 10 sack cement plug spotted from surface in top of 8-5/8" OD casing. Hole will be filled with heavy drilling mud between cement plugs. A piece of 4-inch line pipe extending six foot above ground level will be placed in top plug to serve as marker.

Approved
Except as follows:

Amerada Petroleum Corporation

By

Position Assistant District Superintendent
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By

Title

Name Amerada Petroleum Corporation

Address Roswell Star Route Tatum, New Mexico

1. The first part of the document is a list of names and addresses of the members of the committee.

2. The second part of the document is a list of the names and addresses of the members of the committee who have been elected to the office of the secretary.

3. The third part of the document is a list of the names and addresses of the members of the committee who have been elected to the office of the treasurer.

4. The fourth part of the document is a list of the names and addresses of the members of the committee who have been elected to the office of the clerk.

5. The fifth part of the document is a list of the names and addresses of the members of the committee who have been elected to the office of the auditor.