NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

otice of Intention				
o Change Plans	Notice of Intention to Temporarily Abandon V		tice of Intention Drill Deeper	
OTICE OF INTENTION O PLUG WELL	Notice of Intention to Plug Back		tice of Intention Set Liner	
Notice of Intention o Squeeze	Notice of Intention to Acidize		etice of Intention Shoot (Nitro)	
OTICE OF INTENTION OF GUN PERFORATE	Notice of Intention (Other)	1 (1 - 1 -	otice of Intention Other)	
OIL CONSERVATION COMMIS	SION Hobbs N. Me	xice ce)	December 18,19	54
Gentlemen:				
Following is a Notice of Intent	tion to do certain work as described	below at the No. Mexic	o State C Lease	•••••
Sunray Oil Carporation (Company or Operator)		Wel	Well No. 2 in (Unit)	
NE 1/4 NE 1/4 of Sec.	16 , T 12-5 , R	32-E,NMPM., No.	Caprock - Queen	
(40-acre Subdivision)				
	FULL DETAILS OF PRO	DOORD DI AN OF W	ODIZ	
\ -		HE RULES AND REGU	LATIONS	
State C #2 was dril	lled to a TD of 3165 wi	th no shows of p	roduction. 13-3/	
State C #2 was dril casing is set at 165		th no shows of p	roduction. 13-3/	
State C #2 was dril casing is set at 165 w/125 sacks. Open hel We propose to fill section using tubing 5-1/2" casing down to casing, placing a per	lled to a TD of 3165 wi	th no shows of p 5-1/2" casing : o 3165". mud & place a c. g truck. We proper topes to place : 4" high on the	roduction. 13-3/ is set at 3010' a ement plug in the ose to pull and r a cement plug in	open hole
State C #2 was dril casing is set at 165 w/125 sacks. Open hel We propose to fill section using tubing 5-1/2" casing down to casing, placing a per We propose to level a	lled to a TD of 3165 wirls commented to surface le section from 3010' to the hole with driliing & Halliburton comenting o it's free point. We parament 4" pipe marker, all pits and clean up to	th no shows of p 5-1/2" casing : o 3165". mud & place a c. g truck. We proper topes to place : 4" high on the	roduction. 13-3/is set at 3010' a sement plug in the case to pull and ra cement plug in well location.	nd cemente open hole ecover the
State C #2 was drill casing is set at 165 w/125 sacks. Open helf we propose to fill section using tubing 5-1/2" casing down to casing, placing a per we propose to level a	lled to a TD of 3165 wir '& cemented to surface le section from 3010' to the hole with driling & Halliburton cementing o it's free point. We parament 4" pipe marker, all pits and clean up to	th no shows of p 5-1/2" casing : o 3165". mud & place a case truck. We proper to place : 4" high on the she location.	roduction. 13-3/ is set at 3010' a ement plug in the ese to pull and r a cement plug in well location.	open hole ecover the 13-3/8
State C #2 was dril casing is set at 165 w/125 sacks. Open hel We propose to fill section using tubing 5-1/2" casing down to casing, placing a per We propose to level a Approved	lled to a TD of 3165 wirls cemented to surface le section from 3010' to the hole with driling & Halliburton cementing of the free point. We promanent 4" pipe marker, all pits and clean up to the hole with driling and the hole	th no shows of p 5-1/2" casing: o 3165'. mud & place a case of property of the property of the property of the property of the place of the property of the	ement plug in the case to pull and racement plug in well location.	open hole ecover the the 13-3/8
State C #2 was dril casing is set at 165 w/125 sacks. Open hel We propose to fill section using tubing 5-1/2" casing down to casing, placing a per We propose to level a Approved	lled to a TD of 3165 wire a cemented to surface le section from 3010' to the hole with drilling & Halliburton cementing of it's free point. We promanent 4" pipe marker, all pits and clean up to the section of the sec	th no shows of p 5-1/2" casing: o 3165'. mud & place a case of property of the property of the property of the property of the place of the property of the	ement plug in the ose to pull and rement plug in well location. Company or Operator Locations regarding well	open hole ecover the the 13-3/8

. .