

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. If not approved, the notice will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. Additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Tatum, New Mexico
(Place)

August 5, 1953
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation State EC#1 Well No. 1 in "E" (Company or Operator) (Unit)
SW 1/4 NW 1/4 of Sec. 23, T. 12-S, R. 32-E, NMPM, East Caprock Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

8964' Total Depth. Lime. Finished drilling 7-7/8" hole @ 11:45 AM, 8/4/53. Ran Schlumberger surveys. Ran a drill stem test from 8700' to 8964'. Recovered 450' of drilling mud out with salt water and 900' salt water out with drilling mud. No show of oil or gas. It is our intention to plug and abandon the above well. We will effect the following procedure: Spot a 35 sack cement plug from 8700' to 8976' and a 35 sack cement plug from 9625' to 9513'. Hole will be full of heavy drilling mud. Will run a casing cutter and cut 8-5/8" OD casing at approximate depth of 450'. Pull 8-5/8" OD casing and spot 10 sack cement plug from 296' to 282' and a 10 sack cement plug in the top of the 13-3/8" OD casing. A piece of 4" line pipe will be cemented in top of 13-3/8" OD casing and will extend five feet above ground level to serve as a marker.

Approved....., 19.....
Except as follows: AUG 7 1953

Amerada Petroleum Corporation
By: [Signature]
Position: Assistant District Superintendent
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By: Engineer District I
Title:

Name: Amerada Petroleum Corporation
Address: Roswell Star Route Tatum, New Mexico