

AREA 640 ACRES  
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

The Vickers Petroleum Co., Inc. Box 744 Roswell New Mexico  
Company or Operator Address  
State "N" Well No. 1 in CSS SW of Sec. 29 T. 12 S  
Lease  
R. 32 E N. M. P. M. Caprock Field, Lea County.  
Well is 660 feet south of the north line and 1280 feet east of the east line of section 29  
If State land the oil and gas lease is No. B-10142 Assignment No. B-10142-2  
If patented land the owner is Address  
If Government land the permittee is Address  
The Lessee is The Vickers Petroleum Co., Inc. Address Wichita, Kansas  
Drilling commenced 10-23 1948 Drilling was completed 1-8 1949  
Name of drilling contractor Carper Drilling Co. Address Artesia, New Mexico  
Elevation above sea level at top of casing 4378 feet.  
The information given is to be kept confidential until 19.

## OIL SANDS OR ZONES

No. 1, from 3015 to 3022 No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	26	welded	new	300	Guide				
5	14	8 rd	new	3011	Float				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
9	8 5/8	300	150	Halliburton		
7 3/4	5 1/2	3011	600	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters — Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
4"	20"	TNT solidified	50 qts.	1-3-49	3033-3018	3030

Results of shooting or chemical treatment. There was no fillup before shot. After shooting and cleaning out there was no increase in oil. No water showed.

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 3015 feet, and from feet to feet  
Cable tools were used from 3015 feet to 3061 feet, and from feet to feet

## PRODUCTION

Put to producing dry hole, 19.  
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.  
If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas.  
Rock pressure, lbs. per sq. in.

## EMPLOYEES

J. V. Lapsley, Driller J. D. Berry V. V. Pears, Driller  
V. A. Lapsley, Driller P. S. LeBlanc, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 17th

day of January, 1949

Notary Public

My Commission expires 3/16/49

Roswell, New Mexico 1-11-49 Date

Name Lonnie Temper

Position Production Supt.

Representing The Vickers Petroleum Co., Inc. Company or Operator

Address Box 744 Roswell, New Mexico

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	125	125	Caliche and sand
125	150	25	Caliche
150	1158	1008	Red Bed
1158	1300	142	Red Bed and anhydrite
1300	1453	153	Anhydrite
1453	2348	895	Anhydrite and salt
2348	2772	424	Anhydrite
2772	2955	183	Anhydrite and shale
2955	3015	60	Anhydrite
3015	3022	7	Sand
3022	3055	33	Sand and anhydrite
3055	3061	6	Anhydrite