NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be retuined to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING	
SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
	Lubbook, Texas Nay 2, 1944
Place Date IL CONSERVATION COMMISSION, anta Fe, New Mexico. entlemen: ollowing is a notice of intention to do certain work as described below at the George P. Livermore, Inc. State "F" Well No. 1 in NE/SE/SW	
Sec. 30 , T. 128 , R. 328	, N. M. P. M., Caprock Field,
Lea: County.	
FULL DETAILS OF P	ROPOSED PLAN OF WORK
FOLLOW INSTRUCTIONS IN THE RULI	ES AND REGULATIONS OF THE COMMISSION
internet to miller wall about Moss 9	3047
tart shooting off pipe.	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then
tart shooting off pipe. Expect to recover about 400° of 5	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then
tart shooting off pipe. Expect to recover about 400° of 5	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then above casing left in well and fill halo
tart shooting off pipe. Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then above casing left in well and fill halo
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis: Will cement piece of 4" pipe at 10	heavy mud to about 500' from surface and then above casing left in well and fill hole h with cement to cellar.
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis: Will cement piece of 4" pipe at 10	heavy mud to about 500' from surface and then above casing left in well and fill hole h with cement to cellar.
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis: Will cement piece of 4" pipe at 10	heavy mud to about 500' from surface and then above casing left in well and fill hole h with cement to cellar.
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis: Will cement piece of 4" pipe at 1 arker of location	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then above casing. above casing left in well and fill hole h with cement to cellar. east 4' above mean ground level for exact
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis Will cement piece of 4" pipe at 1sacker of location	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then 2s casing. above casing left in well and fill hole h with cement to cellar. east 4' above mean ground level for exact George P. Livermore, Inc. Company or Operator
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis: Will cement piece of 4" pipe at 1 arker of location	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then 2s casing. above casing left in well and fill hole h with cement to cellar. east 4' above mean ground level for exact George P. Livermore, Inc. Company or Operator
Expect to recover about 400° of 5 Will then spot 15 sacks of cement p to 50° of surface with mud and finis: Will cement piece of 4" pipe at 1 arker of location	with 15 sacks of cement on bottom, T. D. 3034, heavy mud to about 500' from surface and then above casing. above casing left in well and fill hole h with cement to cellar. east 4' above mean ground level for exact

OIL CONSERVATION COMMISSION,

Name George P. Livermore, Inc. 816 Lubbock Nat'l Bldg.

Address Lubbock, Texas