

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

|   |          |  |  |   |  |
|---|----------|--|--|---|--|
| NOTICE OF INTENTION<br>TO CHANGE PLANS  |          | NOTICE OF INTENTION TO<br>TEMPORARILY ABANDON WELL |  | NOTICE OF INTENTION<br>TO DRILL DEEPER  |  |
| NOTICE OF INTENTION<br>TO PLUG WELL     | <b>X</b> | NOTICE OF INTENTION<br>TO PLUG BACK                |  | NOTICE OF INTENTION<br>TO SET LINER     |  |
| NOTICE OF INTENTION<br>TO SQUEEZE       |          | NOTICE OF INTENTION<br>TO ACIDIZE                  |  | NOTICE OF INTENTION<br>TO SHOOT (Nitro) |  |
| NOTICE OF INTENTION<br>TO GUN PERFORATE |          | NOTICE OF INTENTION<br>(OTHER)                     |  | NOTICE OF INTENTION<br>(OTHER)          |  |

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

January 18, 1960

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sunray Mid-Continent Oil Company N. M. State "I" Well No. 2 in J  
(Company or Operator) (Unit)  
NW 1/4 SE 1/4 of Sec. 36, T. 9S, R. 33E, NMPM, Lane Wolfcamp Pool  
(40-acre Subdivision) Lee County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to P&amp;A this well as follows:

1. Run tbg and lead hole w/mud. Lay 10 sx plug on top of Model "D" pkr @ 9640' in 7" csg.
2. Cut off 7" csg @ approx 7700' and pull same.
3. Place 25 sx plug across cut off point.
4. Place 50 sx plug across base of San Andres @ 5335'.
5. Place 25 sx plug across intermediate csg shoe.
6. Place 10 sx plug in top of intern csg.
7. Install 4" x 4' permanent well marker.

Offset leasees have been notified asper attached letter.

Well Status: Surf csg 13 3/8" @ 336' w/cnt circ. Intermediate csg 9 5/8" @ 3999' w/cnt circ.  
7" csg set @ 10,895' w/400 sx in 8 3/4" hole. Temp Survey top cnt @ 7785'. TD  
10,898'. GI retainer @ 9743' w/all perfs below squeezed off. Wolfcamp perfs  
@ 9670'-9683' w/Model "D" Packer @ 9640'.

Approved....., 19.....  
Except as follows:Sunray Mid-Continent Oil Company  
Company or OperatorBy.....  
R.E. StattonPosition.....  
District Engineer  
Send Communications regarding well to:Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....  
EngineerName.....  
G. T. McClanahanAddress.....  
Box 128, Hobbs, New Mexico