

30-025-00760

COUNTY Lee		FIELD Wildcat		STATE N.M.		NC	OWVO
OPR American Mannex Corporation							
NO. 1		LSE Flying "M"-State		MAP			
SEC. 15		T. 9S	R. 33E	SUR. 34		CO. ORD.	
LOC. 660' fr N & W Lines of Sec. 34							
Re-		MI.	FROM	CLASS.	O WDP EL 4373A		
SPUD. 5-12-63		COMP.	8-8-63	FORMATION	DATUM	FORMATION	DATUM
IRI. A 6500							
CSG. & SX.							
5 1/2" 12454' 2000							
TBG. DEPTH		SIZE					
LOGS EL GR RA IND HC A							
		TD 12455'			PB 9250'		
PROD INT.		(DAILY RATE)	BS&W	CH.	GOR	GTY	C. P.
8622-34'		Flo. 192 BO	16/64"		37.5	Pkr	275# 24 h
(Abo)							

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sharp Drlg. Co. PROP DEPTH PB 11,750' type
DATE

F.R. 5-9-63. OWVO, Formerly Trice Production Co.,
Orig. P&A. OTD 12450'. Elevation 4373' L&S
PD 11,750' Atoka
Contractor - Sharp Drlg. Co.
5-20-63 TD 12455', prep to PB & Perf Bough "C"
Perf 11667-681', & 11685-691' W/2 SPF
A W/1000 gals
Swbd 97.26 BAW & Form. Wtr/no time.
5-27-63 TD 12455', PB 9500', prep to squeeze.
Set BP @ 9500', Perf 9420-34' w/4 SPF
A 500 MA
Fld. 96.9 BO + 19.38 BW/16 hrs thru 24/64" chk.
Perf 9417.5-9420.5' W/4 SPF
A All Perfs W/6000 gals
Swbd 69 BF/6 hrs. (80% wtr & 20% oil).

American Mannex Corporation, #1 Flying "M"-State - Sec.
Wildcat 15-9S-33E

6-3-63 TD 12455', PB 9500', swbg.
Squeezed Perfs 9417.5-34' with 100 sx.
Re-Perf 9424-29' W/4 SPF
A W/250 gals, Rec Load & Swbd 25.04 BF/6 hrs
(92% oil).

6-10-63 TD 12455', PB 9500', RU Pump.
Swbd 19.27 BO + 1.25 BW in 10 hrs.

6-17-63 TD 12455', PB 9500', tstg. on pump.
Ppd. 12 BO + 5 BW in 24 hrs.

6-24-63 TD 12455', PB 9500', tstg. on pump.
Ppd. 5.5 BO in 24 hrs.

7-1-63 TD 12455', PB 9500', tstg. on pump.
Re-Ac W/2500 gals
Ppd. 60 BO, no gauge on acid wtr in 24 hrs.
Ppd. 5 BO in 24 hrs.

7-8-63 TD 12455', PB 9500', tstg. on pump.

7-15-63 Ppd. 22 BO in 24 hrs.
TD 12455', PB 9500', tstg. on pump.
Ppd. 6.88 BO + 1 BW in 24 hrs.

7-22-63 TD 12455', PB 9500', tstg. on pump.
SI 24 hrs; Ppd. 16.5 BO in 24 hrs.

7-29-63 TD 12455', PB 9500', SI.
Ppd. 5.5 BO + 5.5 BW in 24 hrs.

8-5-63 TD 12455', PB 9500', SI.

8-12-63 TD 12455', PB 9500', Prep to Perf.
Set BP @ 9400', Perf 9370-81' W/2 SPF
Att. Acidize, would not take.
Re-Perf 9370-81' W/2 SPF, spotted 500 MA
Swbd dry.
Set retainer @ 9250' & Sq. Perfs 9370-81'
with 60 sx.

8-19-63 TD 12455', PB 9250', SI.

American Mannex Corporation, #1 Flying "M"-State - Sec.
Wildcat 15-9S-33E

8-19-63

-continued-

Perf (Abo) 8622-26', 8630-34' W/2 SPF

A W/500 MA.

Swbd 62 BLW + 35 BO (est. cut 15% wtr) in 24
hrs.

8-26-63

TD 12455', PB 9250', SI.

9-3-63

TD 12455', PB 9250', SI.

Re-A W/6000 gals

9-16-63

TD 12455', PB 9250', COMPLETED