

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.
E8834

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dual oil
2. Name of Operator Sunray DX Oil Company
3. Address of Operator P.O. Box 128, Hobbs, New Mexico
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 1 TOWNSHIP 10S RANGE 33E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

N.M. State "F"

9. Well No.

2

10. Field and Pool, or Wildcat

Lane-Penn

15. Elevation (Show whether DF, RT, GR, etc.) 4272 GR

12. County

Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input checked="" type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input type="checkbox"/>		
OTHER	<input type="checkbox"/>		

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Load hole w/mud, place 25 sx cmt. plug over perfs 4607-4669'.
2. Pull 7" csg (Top of cmt 4200' by temp. survey).
3. Place 25 sx cmt. plugs as follows: (a) Top of 7" csg stub
(b) Bottom of 9 5/8" csg (4025')
4. Place 10 sx at surface, out of csg, at GL. Install Dry Hole Marker, fill pits, level location and clear of junk.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>B.F. Brawley</u> B.F. Brawley	TITLE <u>District Engineer</u>	DATE <u>1-13-65</u>
-----------------------------------------	--------------------------------	---------------------

APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		