

COUNTY	Lee	FIELD	South Lane-Penn.	STATE	N.M.	NO.	
OPR.	T. F. Hodge	MAP					
NO.	1	LSE. Humble-State "A"					
SEC.	26	T.	10S	BLK	R	33E	SUR.
				CO-ORD.			
LOC. 2130' fr N Line & 1980' fr W Line of Sec.							
MI.		FROM		CLASS.		EL. 4204'	
SPUD.	4-24-63	COMP.	6-17-63	FORMATION	DATUM	FORMATION	DATUM
TBT. 750 gals acid, Dolofrac 15,000 gals				LOG:			
				Anhy	2020		
CSG. & SX.				Yates	2631		
13 3/8" 334' 350				SA	3894		
8 5/8" 3988' 500				Glor	5339		
4 1/2" 9830' 500				Tubb	6790		
TBG. DEPTH SIZE				Abo	7612		
LOGS EL GR RA IND HC A				Bo. "C"	9720		
				TD	9830'	PB	9759'
PROD INT.		(DAILY RATE)		BS&W	GH	GOR	GTY
9725-36'		Pump 186 BO + 81 BW					40.5
(Bough "C")							24'
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT. DATE				PROP DEPTH 9700' TYPE RT			

F.R. 4-25-63, Bough "C"

PD 9700' RT

4-29-63 Drlg. 3321'.

5-6-63 Drlg. 5642'.

5-13-63 Drlg. 8012'.

5-20-63 TD 8929', fshg.

5-27-63 Drlg. 9500'.

6-3-63 TD 9830' sh., WOC.

6-10-63 TD 9830' sh., WOC.

6-17-63 TD 9830' sh., WOC.

6-24-63 TD 9830' sh., installing Kobe Pump.

Perf 16/9730-34', treated 750 gals acid.

7-1-63 TD 9830' sh., prep to test on pump.

7-8-63 TD 9830' sh., tstg. on pump.

7-15-63 TD 9830' sh., prep to test on pump.

Ppd. 35 BO + tr. wtr in 24 hrs.

Re-Perf 22/9725-36', Dolofrac 15,000 gals.

7-22-63 TD 9830' sh., PB 9759', COMPLETED.