

RECORD OF DRILLING OPERATIONS

1. DELETION OR OTHER ERRORS, TESTS OR DEVIATION MEASURES WERE MADE, STATE ABOVE ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 10140 FEET, AND FROM FEET TO FEET.
 CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.
 * Driller's Total Depth

PRODUCTION

PUT TO PRODUCING September 30, 1962
 OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 644 BARRELS OF LIQUID OF WHICH 43 % WAS OIL; % WAS EMULSION; 57 % WATER; AND % WAS SEDIMENT. A.P.I. GRAVITY 47.50
 GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS
 BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.
 LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (in Conformance With Geographical Section Of State)

SOUTHEASTERN NEW MEXICO		NORTHWESTERN NEW MEXICO	
T. ANTONIO	1930	T. BAYLOR BOUGH "D"	9820
T. SALADO	1987	T. GILSON	9935
B. TANSIL	2552	T. MONTOYA	
T. YATES	2595	T. SIMPSON	
T. QUEEN	3305	T. MCKEE	
T. GRAYSON		T. ELLENBURGER	
T. SAN ANDRES	3868	T. GR. WASH	
T. GLORIETA	5320	T. GRANITE	
T. WHEELBARROW	5398		
T. TUBBS	5790		
T. ABO	7660		
T. WOLF CAMP	8855		
T. BOUGH "C"	9719		

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1780	1780	Red Bed				
1780	2580	800	Red Bed & Anhydrite				
2580	2920	340	Anhydrite & Salt				
2920	3365	445	Anhydrite, Gypsum & Salt				
3365	3905	540	Anhydrite & Salt				
3905	5822	1917	Lime				
5822	6327	505	Lime, Salt & Shale				
6327	7614	1287	Lime				
7614	8011	397	Abo Shale				
8011	8146	135	Shale				
8146	8396	250	Shale & Lime				
8396	9645	1249	Lime				
9645	10140	495	Lime & Shale				
	T.D.						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

November 9, 1962

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2347, Hobbs, New Mexico
 NAME POSITION OR TITLE Agent