



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Sinclair Oil and Gas Company

State 262

(Company or Operator)

(Lease)

Well No. 1, in SW 1/4 of NE 1/4, of Sec. 22, T. 11 S, R. 33E, NMPM.

Wildcat

Pool,

Lea

County.

Well is 1980 feet from North line and 1980 feet from East line

of Section 11. If State Land the Oil and Gas Lease No. is

Drilling Commenced January 4, 1956 Drilling was Completed April 8, 1956

Name of Drilling Contractor Makin Drilling Company

Address Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 4152 The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8	48	N	303				
9 5/8	40 & 36		3874	Halliburton	596		
5 1/2	17	N	10000	Halliburton	7576	9891-9905	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	13 3/8	306	350	Halliburton		
12 1/2	9 5/8	3875	1600	#		
5 1/2	17	10000	500	#		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized with 500 gal mud acid by Western Co.

Result of Production Stimulation Swabbed salt water with rainbow show of oil. well as plug ed and Abandoned 5-14-56.

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 11171 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

PRODUCTION

Put to Producing Plugged & Abandoned 5/14, 1956

OIL WELL: The production during the first 24 hours was None barrels of liquid of which \_\_\_\_\_ % was  
was oil; \_\_\_\_\_ % was emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % was sediment. A.P.I.  
Gravity \_\_\_\_\_

GAS WELL: The production during the first 24 hours was \_\_\_\_\_ M.C.F. plus \_\_\_\_\_ barrels of  
liquid Hydrocarbon. Shut in Pressure \_\_\_\_\_ lbs.

Length of Time Shut in \_\_\_\_\_

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. <u>1633</u>	T. Devonian.	T. Ojo Alamo.	
T. Salt.	T. Silurian.	T. Kirtland-Fruitland.	
B. Salt.	T. Montoya.	T. Farmington.	
T. Yates. <u>2455</u>	T. Simpson.	T. Pictured Cliffs.	
T. 7 Rivers.	T. McKee.	T. Menefee.	
T. Queen. <u>3140</u>	T. Ellenburger.	T. Point Lookout.	
T. Grayburg.	T. Gr. Wash.	T. Mancos.	
T. San Andres. <u>3187</u>	T. Granite.	T. Dakota.	
T. Glorieta. <u>5110</u>	T. _____	T. Morrison.	
T. Drinkard.	T. _____	T. Penn.	
T. Tubbs. <u>6490</u>	T. _____	T. _____	
T. Abo. <u>7308</u>	T. _____	T. _____	
T. Penn. <u>8903</u>	T. _____	T. _____	
T. Miss. <u>10545</u>	T. _____	T. _____	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Surface	960	960	Red bed	10218	10381	63	Lime & Chert
960	1571	611	Red & gyp	10381	10437	56	Lime & Shale
1571	1731	160	Red bed rock	10437	10599	162	Lime
1731	3333	1602	Anhy & Salt	10599	11171	572	Lime & Chert
3333	3717	384	Anhy	11171			T.D.
3717	3810	93	Anhy & lime				
3810	7170	3360	Lime				
7170	7222	52	Lime, Sand, & Shale streaks				
7222	7349	127	Lime & Shale				
7349	7893	544	Shale				
7893	7958	65	Shale & lime				
7958	8496	538	Lime				
8496	8523	27	Lime & Chert				
8523	9763	240	Lime				
9763	9841	78	Lime & Chert				
9841	10135	294	Lime				
10135	10159	24	Lime & Chert				
10159	10218	59	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Sinclair Oil and Gas Co. Address 520 E. Broadway Hobbs, New Mexico  
Name C.C. Salters Position or Title Superintendent