

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mall to Oil Conservation Commission, Santa Fe, New Mexico, or agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

H. S. Moss		Moss State	
Well No. 1	SW SW	32	115
Company or Operator		Lease	
R. 33	N. M. north	Loca	
660	xxxx	east	
660	xxxx	west	
feet south of the North line and		Dec 32	
B-10139		Assignment No.	
If State land the oil and gas lease is No.			
If patented land the owner is			
Address			
If Government land the permittee is			
H. S. Moss			
The Lessee is			
Dec. 22		50	
Drilling commenced		April 30	51
Name of drilling contractor		Address	
Oil States Drilling Company		Dallas, Texas	
Elevation above sea level at top of casing		4284	
not		DF - 4302	
The information given is to be kept confidential until		19	
OIL SANDS OR ZOZES			
No. 1, from	8530	8643 (1st)	9611
No. 4, from	to	9611	9665
No. 2, from	8643	9910	10,001
No. 3, from	9070	11,590	11,610
IMPORTANT WATER SANDS			

Include data on rate of water inflow and elevation to which water rose in hole.

NON TESTED

No. 1, from	to	feet.
No. 2, from	to	feet.
No. 3, from	to	feet.
No. 4, from	to	feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	NAME	AMOUNT	KIND OF SHOE	CGI & FILLED FROM	PERFORMED TO	PURPOSE
13-3-8	40	8	Seamless	Baker			NONE	--
8-5-8 28 & 36		8		356.32			NONE	--
				3837.3				
							Recorded 12861 of 8-5-8 casing	

ADDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	WELL GRAVITY XXXXXX	AMOUNT OF MUD USED
17	13-3-8	356.3	275	Halliburton	7.5	Hole Full
11	8-5-8	3837.3	1000	Halliburton	7.5	Hole Full

PLUGS AND ADAPTERS

Heaving plug—Material	None	Length	Depth Set
Adapters—Material	Size		

RECORD OF SHOOTING OR CHEMICAL TREATMENT

[illegible]

RESULTS OF SHOOTING AT SUNSHINE AFTER CHEMICAL TREATMENT.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

QUESTIONS

Rotary tools were used from _____ feet to _____ feet. 11,630 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet.

EMPLOYEES

J. C. Cox	Driller	J. M. Darnell	Driller
C. L. East	Driller	M. W. Weatherford	Driller

INFORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this _____ day of _____, 1951.

Dallas, Texas

May 5, 1951

day of May 1951

POISSON

Dallas County, Texas

Company or Operator.

Address _____
1503 First National Bank Building

SEXAL '7 SELLER

FORMATION RECORD

FORMATION		THICKNESS IN FEET	FORMATION	
FROM	TO			
0	1477	1477	Red Bed Sand Shale	
1477	1620	143	Red Bed	
1620	1702	82	Anhydrite	
1702	2353	651	Shale & Anhydrite	
2353	2574	221	Shale & Sand	
2574	3743	169	Anhydrite - grey shale & Sand	
3743	7320	3577	Lime & Sand	
7320	8440	1120	Shale & Dolomite	
8440	9280	840	Dolomite & Lime	
9280	9860	580	Lime & Shaley Lime	
9860	10292	432	Lime, Shale, Chert & Sand	
10292	10860	568	Grey lime, Black & Brown shale, Sandy Lime	
10860	11575	715	& Chert Lime, Shale, Chert, Sand & Limy Shale	
11575	11630	55	Dolomite	