

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

FEB 21 1951

OIL CONSERVATION COMMISSION
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

February 19, 1951

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation State of **TX** Well No. **1** in the
C/SW/4 SW/4 Company or Operator **34** Lease **11-3** R. **33-E** N. M. P. M.,
Bagley-Silure/Devonian of Sec. **34**, T. **11-3**, R. **33-E**, Lea County.
 Field **February 18, 1951**

The dates of this work were as follows:

Notice of intention to do the work was ~~was not~~ submitted on Form C-102 on **February 18,** 19 **51**
 and approval of the proposed plan was ~~was not~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3790' - Total Depth - Line. Ran 104 Joints of 8-5/8" O.D., 32#, Grade J-55, 8-Rd. Thd., Range 2 & 3, S.S. New & S.H. Casing, set at 3790' and cemented with 1450 sacks Regular cement of which 1000 sacks were mixed with 3% Jell and 50 sacks Inocer cement - Total of 1500 sacks. Plug to 3723' at 8:00 P.M., 2-18-51. Maximum pump pressure 1500#. 2 Baker Centralizers at 3745' & 3775' and 4 Weatherford Scratchers at 3750', 3760', 3770' and 3780'.

Witnessed by **C. E. Telge** **Amerada Petroleum Corporation** Foreman
 Name Company Title

Subscribed and sworn before me this.....

19th day of February, 1951

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **Don Tipton**Position **Assistant District Superintendent**Representing **Amerada Petroleum Corporation**
Company or OperatorAddress **Drawer D, Monument, New Mexico**My commission expires **10-11-54**

Remarks:

FEB 21 1951

Ray Spence
 Name
 Oil & Gas Inspector
 Title

