

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Form C-102  
RECEIVED  
OIL CONSERVATION COMMISSION

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work contemplated is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	<input type="checkbox"/>	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	<input type="checkbox"/>	

Monument, New Mexico

October 17, 1951

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the

**Amerada Petroleum Corporation** State BT<sup>MM</sup> Well No. **1** in **C/SE/4 NE/4**  
 Company or Operator **11-S** Lease **33-E** **Bagley-Siluro/Devonian** Field.  
 of Sec. **Lea**, T. \_\_\_\_\_, R. \_\_\_\_\_, N. M. P. M. \_\_\_\_\_ County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

11040' - Total Depth - Lime - Finished drilling 7-7/8" hole at 5:45 AM, 10/13/51. Ran Schlumberger's Electrical, Gamma Ray, Microlog & Lateral Surveys. Ran 5 1/2" Csgs. as follows:

46 Jts	(1998.55')	5 1/2" OD 17" N80 R-3 8-RT SS Csg., New, LT&C
269 Jts	(7937.99')	5 1/2" OD 17" J-55 R-2 8-RT Italian SS Csg., New ST&C
2 Jts	(79.67')	5 1/2" OD 17" J-55 R-3 8-RT Spang SS Csg., New, LT&C
2 Jts	(86.17')	5 1/2" OD 17" Gr-8640 R-3 8-RT SS Csg., New LT&C
22 Jts	(921.37')	5 1/2" OD 17" N-80 R-3 8-RT SS Csg., New, LT&C
341 "	11023.75'	

Casing set @ 11040' with 600 sacks Slow-set Cement mixed 3% Jel and 1/4" Flo-Seal per sack. Plug to 10951' @ 9 PM, 10/16/51. Maximum pump pressure, 1750#. Ran 10 Baker Centralizers spaced 30' apart from 8968' to 9058, from 9760' to 9850' and from 11000' to 11030'. Ran 20 Weatherford Scratchers spaced 15' apart in the above sections. After W.O.C. for approximately 24 hours we will test casing shut-off.

Approved \_\_\_\_\_, 19\_\_\_\_\_  
except at follows:

**Amerada Petroleum Corporation**  
Company or Operator

By \_\_\_\_\_  
 Position **Assistant District Superintendent**  
 Send communications regarding well to  
 Name **Amerada Petroleum Corporation**  
 Address **Drawer 3, Monument, New Mexico**

OIL CONSERVATION COMMISSION

By *[Signature]*  
 Title **Oil & Gas Inspector**