

OIL CONSERVATION DIVISION

P. O. BOX 2086

SANTA FE, NEW MEXICO 87501

Form O-101
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

1. Industry Type of Lease	
State ☒ New Mexico	
2. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM O-101) FOR SUCH PROPOSALS.OIL WELL ☐ GAS WELL ☐ OTHER ☒ TA Lost LeaseName of Operator
AMERADA HESS CORPORATIONAddress of Operator
Drawer D, Monument, New Mexico 88265Location of well
UNIT LETTER 0 990 FEET FROM THE South LINE AND 2310 FEET FROM
East LINE, SECTION 34 TOWNSHIP 11S RANGE 33E NMPM.

7. Unit Agreement Name

8. Form or Lease Name

State BT "O" Gas Comm.

9. Well No.

1

10. Field and Pool, or Wildcat

12. County

Lea

15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:FORM REMEDIAL WORK ☐TEMPORARILY ABANDON ☐L OR ALTER CASING ☐OTHER ☐PLUG AND ABANDON ☒CHANGE PLANS ☐REMEDIAL WORK ☐COMMENCE DRILLING OPNS. ☐CASING TEST AND CEMENT JOB ☐OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to pull 2-1/16" tbg. & pkr. Run cement retainer on tbg. & set at 8670'. Squeeze Penn. zone thru 5 1/2" csg. perf. fr. 8774' to 8798', 8808' to 8834', 9766' to 9820' & cap retainer w/at least 35' of cement. Load hole w/salt gel. mud. Run free point & cut off & pull 5 1/2" csg. Top of cement by temp. survey at 6336'. Spot cement plug 50' in & 50' out of top of 5 1/2" cut off csg. Spot 100' of cement across top of Glorieta at 5119'. Spot cement plug 50' above and 50' below 8-5/8" csg. shoe at 3790'. Spot 100' cement plug across top of salt at 1737'. Spot 10 sks. cement in top of 8-5/8" csg. Cut off 13-3/8" & 8-5/8" at surface. Install dry hole marker, remove all facilities & level location.

THIS DOCUMENT IS NOT TO BE USED AS
EVIDENCE IN THE ENFORCEMENT OF
ANY OF THE PROVISIONS OF THE G-103
TO BE APPROVED.

Exp. 12-10-17

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. B. Sikes</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>6-8-79</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist 1, Supv.</u>	DATE <u>JUN 12 1979</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUN 11 1979

OIL CONSERVATION COMM.
HOBBS, N. M.