

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is begun. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Tatum, New Mexico  
(Place)

January 22, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Tatum, New Mexico

Amerada Petroleum Corporation State B.T."C" Well No. 1 in N  
(Company or Operator) (Unit)  
SE/4 1/4 SW/4 1/4 of Sec. 35, T. 11-S, R. 33-E, NMPM., Bagley Silure Devonian Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Present Total Depth 10,980' DCD 10,979' 7-5/8" OD Casing perforations from 10,959' to 10,979'  
INTENSIONS: Pull 2-3/8" OD FUE Tubing and flow Valves, Set bridge plug @ 10,950' with 1 sz.  
cement on top. Perforate 7-5/8" OD Casing from 10,920' - 10,935' & 10,860'-10,885' and from  
10,787'-10,830' with 2 shots per ft. Set wire line production packers @ 10,910', 10,845' &  
10,780'. Run 2-3/8" OD Tubing with necessary landing nipple and sliding sleeve nipples to treat  
and produce each section separately. Acidize each section with 500 gallons regular acid.  
Set necessary side door nipples and produce thru bottom set of perforations from 10,920'-10,935'  
separately and resume production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

Amerada Petroleum Corporation

Company or Operator

By.....

Position..... Assistant District Superintendent

Send Communications regarding well to:

Name..... Amerada Petroleum Corporation

Address..... Roswell Star Route - Tatum, New Mexico

