

## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	<b>X</b>
NOTICE OF INTENTION TO DEEPEN WELL			

Momentum, New Mexico

August 7, 1950

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_  
**Amerada Petroleum Corporation** State BT "C" Well No. **2** in **C/NW/4/SE/4**  
 Company or Operator Lease  
 of Sec. **35**, T. **11-S**, R. **33-E**, N. M. P. M., **Bagley-Siluro/Devonian** Field.  
**Lea** County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

**11,715' - Total Depth - Line. Finished drilling 7-3/8" hole at 4:00 P.M., 8-6-50. No oil or gas zones of consequence were encountered. It is our intention to plug and abandon this well, after running Schlumberger's Electrical, Gamma Ray & Dipmeter Surveys. We propose to plug the well as follows: 35 sacks of cement from total depth to approx. 11575', 35 sacks of cement from 8810' to 8670', 35 sacks of cement from 3800' to 3688', 25 sacks of cement from 1430' to 1349'. Cut off 8-5/8" casing at approximately 1320' & recover same. 35 sacks of cement from 315' to 270' into 13-3/8" O.D. Casing, ~~SHUT-OFF~~ then dump 10 sacks of cement in top of the 13-3/8" surface casing. Set a piece of 4" Line Pipe, cemented in center of surface casing, extending 5' above surface of the ground. Heavy mud between all above cement plugs.**

Approved AUG - 9 1950, 19\_\_\_\_  
 except as follows:

**Amerada Petroleum Corporation**

Company or Operator

By *Don Topp*

Position **Assistant District Superintendent**  
 Send Communications regarding well to

Name **Amerada Petroleum Corporation**Address **Drawer D, Momentum, New Mexico**

OIL CONSERVATION COMMISSION,

By *Ray Garbrough*  
 Title *Oil & Gas Inspector*