

**DUPLICATE**

RECEIVED  
AUG 1960  
NATIONAL COMMISSION  
ON CONSERVATION COMMISSION  
HOBBS-OFFICE

T  
L  
S

**WELL RECORD**

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.**

**Amerada Petroleum Corporation**

**Drawer D. Monument. New Mexico**

State BT "C" Company or Operator  
Well No. 2 in C/WM/4 NE/4 of Sec. 35 Address 11-9  
Lease 33-E Bagley-Silure/Devonian Lea County.  
N. M. P. M. 660 1900 feet south of the North line and 1900 feet west of the East line of Section 35  
Well is feet south of the North line and feet west of the East line of Section 35  
If State land the oil and gas lease is No. B-1347 Assignment No.  
If patented land the owner is, Address  
If Government land the permittee is, Address  
The Lessee is Amerada Petroleum Corporation P.O. Box 2040, Tulsa 2, Okla.  
Address  
Drilling commenced March 27, 1950 Drilling was completed August 6, 1950  
Name of drilling contractor Noble Drilling Corporation Address Tulsa, Oklahoma  
Elevation above sea level at top of casing 4228 feet.  
The information given is to be kept confidential until Not Confidential 19

### OIL SANDS OR ZONES

<b>None</b>			
No. 1, from.....	to.....	No. 4, from.....	to.....
No. 2, from.....	to.....	No. 5, from.....	to.....
No. 3, from.....	to.....	No. 6, from.....	to.....

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet. ....

No. 2, from.....to.....feet. ....

No. 3, from.....to.....feet. ....

No. 4, from.....to.....feet. ....

## CASING RECORD

[illegible]

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2"	13-3/8"	905'	225	Halliburton		
7-3/8"	8-5/8"	3889'	1500	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material..... Length..... Depth Set.....  
Adapters — Material..... Size.....

### RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
			<b>None</b>			

Results of shooting or chemical treatment.....

### RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to 11,715' feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

## PRODUCTION

Put to producing.....**Dry Hole - Plugged & Abandoned**.....

The production of the first 24 hours was.....barrels of fluid of which.....% was oil; .....% emulsion; .....% water; and.....% sediment. Gravity, Be.....

If gas well, cu. ft. per 24 hours.....Gallons gasoline per 1,000 cu. ft. of gas.....

Rock pressure, lbs. per sq. in.....

## EMPLOYEES

<b>E. W. Yoder</b> .....	Driller	<b>Ace Williams</b> .....	Driller
<b>Curtis L. Shores</b> .....	Driller	.....	Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11th  
day of August, 1950

Monument, New Mexico August 11, 1950

Name Don Lopez  
Position Assistant District Superintendent

Representing **Amorada Petroleum Corporation**

Company or Operator  
Address **Drawer D, Monument, New Mexico**

My Commission expires.....**10-24-53**

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	19	19	Cellar
19	212	193	Sand, Caliche & Lime
212	1790	1578	Red Bed, Sand & Shale
1790	1850	60	Shale, Sand & Anhydrite
1850	3800	1950	Sand, Shale, Salt & Anhydrite
3800	4570	770	Dolomite & Anhydrite
4570	5010	440	Limestone
5010	5240	230	Dolomite & Anhydrite
5240	5970	730	Dolomite, Anhydrite, Salt & Shale
5970	6720	750	Dolomite & Anhydrite
6720	7400	680	Dolomite, Anhydrite, Sand & Salt
7400	8270	870	Shale, Dolomite & Anhydrite
8270	8525	255	Dolomite & Anhydrite
8525	8680	155	Dolomite & Chert
8680	10585	1905	Sinestone, Chert & Shale
10585	10835	250	Sand, Shale & Lime
10835	11300	465	Chert, Shale & Lime
11300	11555	255	Limestone & Shale
11555	11610	55	Sand, Limestone & Shale
11610	11621	11	Shale, Limestone, Sand & Chert
11621	11650	29	Limestone, Shale, Sand, Chert & Dolomite
11650	11715	65	Dolomite & Chert

GEOLOGICAL DATE

Top Anhydrite	1787'
Top Salt	1842'
Base Salt	2433'
Top Yates	2524'
Base Yates	2643'
Top Red Sand	3225'
Top San Andres	3804'
Base San Andres	5207'
Top Paddock	5503'
Top Clear Fork	5985'
Top Abe	7382'
Top Wolfcamp	8552'
Top Pennsylvanian	8810'
Top Mississippian (Est.)	10825'
Top Devonian	11610'

SLOPE TESTS

850'	-1/4 Deg.
1225'	-1/4 "
1700'	-1/2 "
1915'	0 "
2300'	-3/4 "
2900'	-3/4 "
3510'	1- "
4000'	1-1/4 "
4600'	2- "
5015'	2-1/4 "
5505'	2- "
6020'	2-1/2 "
6542'	2-1/4 "
7090'	2-1/2 "
7515'	2- "
7950'	2-3/4 "
8355'	2-3/4 "
8973'	1-3/4 "
9440'	1-1/4 "
9701'	1-1/2 "
10265'	2-1/2 "
10428'	1-1/2 "
10748'	3-1/4 "