

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

April 6, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State **ETC** Well No. **2** in the _____

Company or Operator _____ Lease _____
C/W/4 SE/4 of Sec. **35**, T. **11-S**, R. **33-E**, N. M. P. M.,
Bagley-Siluro/Devonian Field, _____ Lea County.

The dates of this work were as follows: **April 5, 1950**

Notice of intention to do the work was ~~(submitted)~~ submitted on Form C-102 on **April 5,** 19**50**
and approval of the proposed plan was ~~(obtained)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3889' - Total Depth - Line. Ran Schlumberger Electrical Survey and Gamma-Ray. Schlumberger checked bottom at 3888'. Ran 102 Joints, 3899.26', threads off measurement, 8-5/8" O.D., 32#, 8-Rd. Thd., Grade J-55, Range 3, S. S. New casing - set at 3889' and cemented with 1000 Sacks Regular Cement mixed 3% Jell, 450 sacks regular cement and 50 sacks Inner cement. Total of 1500 sack Plug to 3808' at 6:10 P.M., 4-5-50. Maximum pump pressure 1400#.

Witnessed by C. E. Telge	Amerada Petroleum Corporation	Farm Boss
Name	Company	Title

Subscribed and sworn before me this _____
6th day of **April** 19**50**

Notary Public

I hereby swear or affirm that the information given above is true and correct.
Name _____
Position **Assistant District Superintendent**
Representing **Amerada Petroleum Corporation**
Company or Operator
Address **Drawer D, Monument, New Mexico**

My commission expires **10-24-53**

Remarks:

APPROVED

NOEL E. HARRIS
Name
Title