

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

RECEIVED

APR 10 1951

OIL CONSERVATION COMMISSION

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

April 6, 1951

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

**Amerada Petroleum Corporation** State **BT "C"** Well No. **3** in the \_\_\_\_\_

Company or Operator

Lease

**C/W/4 SW/4** of Sec. **35**, T. **11-S**, R. **33-E**, N. M. P. M.,

**Bagley-Silure/Devonian** Field **Lea** County.

The dates of this work were as follows: **April 5, 1951**

Notice of intention to do the work was (~~waived~~) submitted on Form C-102 on **April 5, 1951**

and approval of the proposed plan was (~~waived~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**10,965' - Total Depth - Line. Ran Schlumberger's Electrical, Gamma Ray & Microlog Surveys. Ran 271 Jts., 10,883.22', 5-1/2" O.D., 17#, S.S. New Casing - Set at 10,895' & cemented W/600 sack of Trinity Refracto cement, mixed W/3% Jell & 1/4# Flow Seal per sack. Plug to 10,796' at 7:00 P.M., 4-5-51. Maximum pump pressure 1750#. Ran 28 Baker centralizers, spaced 30' apart, in the following sections: from 8880' to 9420'; 9720' to 9810' and from 10760' to 10880'. Ran 53 Weatherford Scratchers spaced 15' apart in above sections.**

Witnessed by **L. V. Stephenson** **Amerada Petroleum Corporation** **Paraman**

Name

Company

Title

Subscribed and sworn before me this \_\_\_\_\_

**6th** day of **April**, 19 **51**

*[Signature]*

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name *[Signature]*

Position **Assistant District Superintendent**

Representing **Amerada Petroleum Corporation**

Company or Operator

My commission expires **10-11-54**

Address **Drawer D, Monument, New Mexico**

Remarks:

**APPROVED**  
**APR 10 1951**

Date \_\_\_\_\_

*[Signature]*  
Name  
Oil & Gas Inspector

Handwritten text at the top of the page, possibly a title or header.

Handwritten text in the upper middle section of the page.

Handwritten text in the middle section of the page.

Handwritten text in the lower middle section of the page.

Handwritten text in the lower section of the page.

Handwritten text at the bottom of the page.