
## NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELL



Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS  REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL			REPORT ON REPAIRING WELL  REPORT ON PULLING OR OTHERWISE ALTERING CASING		
REPORT ON RESULT OF TEST OF CASING SHUT-OFF			REPORT ON DEEPENING WELL		
REPORT ON RESULT OF PLUGG	ING OF WEL				
			1050	Monument, New Maxi	<b>~</b>
		anuary	1952 Date		ice
Following is a report on the work do	one and the res	sults obtained i	under the headir	ng noted above at the	
merada Petroleum Corpora	ation	State B	P# C#		in tl
Company or Ope		15	Lease , T. <b>ll-S</b>	, R <b>33F</b>	, N. M. P. M
agley-Pennsylvanian				<del></del>	
The dates of this work were as follo					
			_		
80' - Total Depth - Lime casing at 250' - F	as (mass) of D ACCOUNT  Ran Telegraphic of a	obtained. (Crossof WORK Description of WORK De	s out incorrect voone and re Survey - Toalculated	vords.) SULTS OBTAINED Sop of cement outside fill, 85.8%. Checked	of <b>\$-5/8</b>   top <b>e</b> f
nd approval of the proposed plan w  DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5, no pressure drop.	as (many) of ACCOUNT  Ran Telestio of a 88 easing  Drilled	obtained. (Crossoft WORK 1)  mperature setual to ( at 3700)  coment from	s out incorrect volume and research and restaulated on 3700 to	vords.) SULTS OBTAINED op of cement outside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin	of \$-5/8' top of 1/2 hour g with
nd approval of the proposed plan w  DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5, no pressure drop.	as (many) of ACCOUNT  Ran Tellish easing Drilled  T - No pro	obtained. (Crossoft WORK 1)  mperature setual to ( at 3700)  coment from	s out incorrect volume and research and restaulated on 3700 to	vords.) SULTS OBTAINED Op of cement outside fill, 85.8%. Checked asing with 1200# for	of \$-5/8' top of 1/2 hour g with
BO' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200# for 1/2 hour	as (many) of ACCOUNT  Ran Tellish easing Drilled  T - No pro	obtained. (Crossoft WORK 1)  mperature setual to ( at 3700)  coment from	s out incorrect volume and research and restaulated on 3700 to	vords.) SULTS OBTAINED op of cement outside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin	of \$-5/8" top of 1/2 hour g with
BO' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200# for 1/2 hour	as (many) of ACCOUNT  Ran Tellish easing Drilled  T - No pro	obtained. (Crossoft WORK 1)  mperature setual to ( at 3700)  coment from	s out incorrect volume and research and restaulated on 3700 to	vords.) SULTS OBTAINED op of cement outside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin	of \$-5/8" top of 1/2 hour g with
BO' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200# for 1/2 hour	as (many) of ACCOUNT  Ran Tellish easing Drilled  T - No pro	obtained. (Crossoft WORK 1)  mperature setual to ( at 3700)  coment from	s out incorrect volume and research and restaulated on 3700 to	vords.) SULTS OBTAINED op of cement outside fill, 85.8%. Checked asing with 1200# for 3780! - Tested casin	of \$-5/8" top of 1/2 hour g with
BO' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200# for 1/2 hour	as (many) of ACCOUNT  Ran Tellish easing Drilled  T - No pro	obtained. (Crossoft WORK 1)  mperature setual to ( at 3700)  coment from	s out incorrect volume and research and restaulated on 3700 to	vords.) SULTS OBTAINED op of cement outside fill, 85.8%. Checked asing with 1200# for 3780! - Tested casin	of \$-5/8" top of 1/2 hour g with
DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200f fer 1/2 hour hole at 12 Noon, 1	as (many) of ACCOUNT  Ratio of a Ratio of a Parity of	obtained. (Crossoft WORK E	s out incorrect volume and reservey - Total culated com 3700 to Started	vords.) SULTS OBTAINED  Sp of cement outside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin drilling formation a	of \$-5/8" top of 1/2 hour g with nd 7-7/8"
DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5, no pressure drop. 1200# fer 1/2 hour hole at 12 Noon, 1	as (many) of ACCOUNT  Ratio of a Ratio of a Parity of	obtained. (Crossoft WORK E	Survey - Total Calculated Tested Company Company	vords.) SULTS OBTAINED  op of cement outside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin drilling formation a	of \$-5/8" I top of 1/2 hour g with nd 7-7/8"
DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200f fer 1/2 hour hole at 12 Noon, 1	as (mass) of a Account  Ratio of a 8 easing Drilled  - ne pre- 12/31/51	obtained. (Crossoft WORK E	Survey - Total Calculated Tested Company Company	cords.) SULTS OBTAINED  Sport cement cutside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin drilling formation a	of \$-5/8" top of 1/2 hour g with and 7-7/8"
DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200/ fer 1/2 hour hole at 12 Noon, I	as (mass) of a Account  Ratio of a 8 easing Drilled  - no pre- 12/31/51	obtained. (Cross of WORK I	Sarvey - Toloulated Tested com 3700 to Started I hereby swea	cords.) SULTS OBTAINED  Sport cement cutside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin drilling formation a	of \$-5/8" top of 1/2 hour g with and 7-7/8"
DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200/ fer 1/2 hour hole at 12 Noon, I	as (mass) of a Account  Ratio of a 8 easing Drilled  - no pre- 12/31/51	obtained. (Crossoft WORK E	Survey - Toalculated Tested com 3700 to Started  I hereby sweatis true and con Name	cords.) SULTS OBTAINED  Sport cement cutside fill, 85.8%. Checked asing with 1200# for 3780' - Tested casin drilling formation a	of \$-5/8"  top of  1/2 hour  g with  nd 7-7/8"  Title
DETAILE  80' - Total Depth - Lime casing at 250' - I cement inside 8-5/ no pressure drop. 1200/ fer 1/2 hour hole at 12 Noon, I	as (mass) of a Account  Ratio of a 8 easing Drilled  - no pre- 12/31/51	obtained. (Cross of WORK I	Survey - Toolealated Tested com 3700 to Started I hereby sweatis true and com Position	poration Farm Farm For or affirm that the information rect.	of \$-5/8"  top of  1/2 hour  g with  nd 7-7/8"  on given above