			<b></b>	F'O	rm C-10
NEW MEXICO OIL		ERVATION COM E <b>W MEXICO</b>	MISSION	RECEN	<u> </u>
MISCELL	ANEC	<b>US NOTIC</b>	ES	- <u>11</u> 10 - 11 - 11	29
Submit this notice in triplicate to the Oil Conserva begin. A copy will be returned to the sender on advisable, or the rejection by the Commission or as and work should not begin until approval is obta the Commission.	which will gent of th	be given the appr	oval, with any r	he work specified	idered.
	re of notic	e by checking below	V:	an an an an Suite Charles an Anna an An	.∦યરજીવ્યું તે ગોવરામાં અને
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	NOTICE OF INT	ENTION TO SH 7 TREAT WELI	OOT OR	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INT OTHERWISE	ENTION TO PU ALTER CASIN		
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INT	ENTION TO PL	UG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			<u> </u>		
lio	mument,	New Maxico	Decem	bor 31, 1951	
Following is a notice of intention to do certain wor Amerada Petrolaum Corporation Sta	rk as desci te BT*C	ribed below at the	177.11	4 . C/SW	/4 SV
Following is a notice of intention to do certain wor Amerada Petroleum Corporation Sta	rk as desci te BT*C	ribed below at the	••••••	4 C/SW	/). SV
Company or Operator Ta				in.	
of Sec	, N	. M. P. M.,	ey-relisylv		Field.
Count	у.				
FULL DETAILS O	OF PROF	OSED PLAN O	F WORK		
FOLLOW INSTRUCTIONS IN THE	RULES A	ND REGULATION		MISSION	
FOLLOW INSTRUCTIONS IN THE 3780! - Tatal Death - Line, Finishe			S OF THE COM	- ·	
3780' - Total Depth - Lime. Finishe			S OF THE COM	- ·	
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.48')	d drill: 32# J-	ing ll" hole a 55 B-2 & R-3 6	S OF THE COM t 9:15 AN, 2 RT SS Ceg.	12/29/ <b>31.</b> Xev	
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.48')	d drill: 32# J-	ing ll" hole a 55 B-2 & R-3 6	S OF THE COM t 9:15 AN, 2 RT SS Ceg.	12/29/ <b>31.</b> Xev	
3780' - Total Depth - Lime, Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93	d drill: 32# J- 32# J- ') 32#	ing 11" hole a 55 R-2 & R-3 6 55 R-2 Italian J-55 R-3 SS Ca	S OF THE COM t 9:15 AN, 1 -RT SS Csg. 8-RT Csg. 1 5. New	12/29/ <b>31.</b> Xev	
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.46') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19'	d drill: 32# J- 32# J- ) 32# J ) 24# J	ing ll" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 85 Ca -55 R-3 8-RT 8	S OF THE COM t 9:15 AN, 1 -RT SS Csg. 8-RT Csg. 5 S Csg. New S Csg. New	12/29/ <b>31.</b> Xev	
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.46') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (489.12'	d drill: 32# J- 32# J- ) 32# J- ) 32# J ) 32# B	ing ll" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 85 Ca -55 R-3 8-RT 8	S OF THE COM t 9:15 AN, 1 -RT SS Csg. 8-RT Csg. 5 S Csg. New S Csg. New	12/29/ <b>31.</b> Xev	
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.46') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19'	d drill: 32# J- 32# J- ) 32# J- ) 32# J ) 32# B	ing ll" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 85 Ca -55 R-3 8-RT 8	S OF THE COM t 9:15 AN, 1 -RT SS Csg. 8-RT Csg. 5 S Csg. New S Csg. New	12/29/ <b>31.</b> Xev	
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>489.12'</u> 96 " 3767.59'	d dr111: 32# J- 32# J- ) 32# ) 32# J ) 32# B	ing ll" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 85 Ca -55 R-3 8-RT 8 -3 J-55 8-RT 8	S OF THE COM t 9:15 AN, 2 -RT SS Csg. 8-RT Csg. 9. New S Csg. New S Csg. New S Csg. New	12/29/ <b>31.</b> New New	65 79/
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.46') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (489.12'	d dr111: 32# J- 32# J- ) 32# ) 32# J ) 32# B 0 sacks	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT S -3 J-55 8-RT S regular comen	S OF THE COM t 9:15 AM, -RT SS Ceg. 8-RT Csg. 9. New S Csg. New S Csg. New S Csg. New S Csg. New S Csg. New	12/29/31. New New Jel, 450 sad	
3780' - Tetal Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 " 3767.59' Casing set at 3780' with 100	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT S -3 J-55 8-RT S regular cemen 3700' at 12:0	s of the com t 9:15 AN, 1 -RT SS Csg. d-RT Csg. s Csg. New S Csg. New S Csg. New t mixed 35 1 AM, 12/30	12/29/31. New New Jel, 450 saci /51. Max pr	essur (
3780' - Tetal Depth - Lime. Finishe Ran 8-\$/\$" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor comput.	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT S -3 J-55 8-RT S regular cemen 3700' at 12:0	s of the com t 9:15 AN, 1 -RT SS Csg. d-RT Csg. s Csg. New S Csg. New S Csg. New t mixed 35 1 AM, 12/30	12/29/31. New New Jel, 450 saci /51. Max pr	essur (
3780' - Tetal Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor comput. 1300#. After W.O.C. for app	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT S -3 J-55 8-RT S regular cemen 3700' at 12:0	s of the com t 9:15 AN, 1 -RT SS Csg. d-RT Csg. s Csg. New S Csg. New S Csg. New t mixed 35 1 AM, 12/30	12/29/31. New New Jel, 450 saci /51. Max pr	essur (
3780' - Tetal Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor comput. 1300#. After W.O.C. for app	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT S -3 J-55 8-RT S regular cemen 3700' at 12:0	s of the com t 9:15 AN, 1 -RT SS Csg. d-RT Csg. s Csg. New S Csg. New S Csg. New t mixed 35 1 AM, 12/30	12/29/31. New New Jel, 450 saci /51. Max pr	essur (
3780' - Total Depth - Lime. Finishe Ram 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 * 3767.59' Casing set at 3780' with 100 and 50 sacks Incor comput. 1300#. After W.O.C. for app	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT 8 -3 J-55 8-RT 8 regular cemen 3700' at 12:0 ely 24 hours b	S OF THE COM t 9:15 AN, 1 -RT SS Ceg. 8-RT Ceg. 5 Ceg. New S Ceg. New S Ceg. New S Ceg. New t mixed 3% 1 AN, 12/30 rill test fo	12/29/31. New New Jel, 450 sad /51. Max pr r casing shu	essur (
3780' - Tetal Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor comput. 1300#. After W.O.C. for app	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT 8 -3 J-55 8-RT 8 regular cemen 3700' at 12:0 ely 24 hours b	s of the com t 9:15 AN, 1 -RT SS Csg. d-RT Csg. s Csg. New S Csg. New S Csg. New t mixed 35 1 AM, 12/30	12/29/31. New New Jel, 450 sad /51. Max pr r casing shu poration	essur (
3780' - Total Depth - Lime. Finishe Ran 8-\$/\$" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (A89.12' 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor commt. 1300#. After W.O.C. for app JAN 3 1952	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 8 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 8-RT 8 -3 J-55 8-RT 8 regular cemen 3700' at 12:0 ely 24 hours b	S OF THE COM t 9:15 AN, 1 -RT SS Ceg. 8-RT Ceg. 5 Csg. New S Csg. New S Csg. New S Csg. New t mixed 35 1 AN, 12/30 rill test fo	12/29/31. New New Jel, 450 sad /51. Max pr r casing shu poration	essur (
3780' - Total Depth - Lime. Finishe Ran 8-\$/\$" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (A89.12' 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor commt. 1300#. After W.O.C. for app JAN 3 1952	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing ll" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 &S Ca -3 J-55 &-RT & regular cemen 3700' at 12:0 ely 24 hours b Amerada Pe By	s OF THE COM t 9:15 AN, -RT SS Ceg. 8-RT Ceg. 5 Csg. New 5 Csg. New 5 Csg. New 5 Csg. New 5 Csg. New t mixed 35 1 AN, 12/30 fill test fo troleum Cor Company of Au	12/29/31. Hew New Jel, 450 sach /51. Max pro- r casing shur poration r Operator	essur L-àrr
3780' - Total Depth - Lime. Finishe Ran 8-\$/\$" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (A89.12' 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor commt. 1300#. After W.O.C. for app JAN 3 1952	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing ll" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 &S Ca -3 J-55 &-RT & regular cemen 3700' at 12:0 ely 24 hours b Amerada Pe By	s OF THE COM t 9:15 AN, -RT SS Ceg. 8-RT Ceg. 5 Csg. New 5 Csg. New 5 Csg. New 5 Csg. New 5 Csg. New t mixed 35 1 AN, 12/30 fill test fo troleum Cor Company of Au	12/29/31. New New Jel, 450 sad /51. Max pr r casing shu poration	essur L-àrr
3780' - Total Depth - Lime. Finishe Ran 8-\$/\$" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (A89.12' 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor commt. 1300#. After W.O.C. for app JAN 3 1952	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 &-RT S -3 J-55 &-RT S regular cemen 3700' at 12:0 ely 24 hours w Amerada Pe By Position Assis	S OF THE COM A 9:15 AN, A -RT SS Ceg. S -RT Csg. S Csg. New S Csg. New S Csg. New S Csg. New A mixed 3% AN, 12/30 rill test fo AN, 12/30 rill test fo Company of Art Total Strip Stant Distri	12/29/31. Hew New Jel, 450 sach /51. Max pro- r casing shur poration r Operator	essur L-àff,
3780' - Total Depth - Lime. Finishe Ran 8-\$/\$" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts (A89.12' 96 " 3767.59' Casing set at 3780' with 100 and 50 sacks Incor commt. 1300#. After W.O.C. for app JAN 3 1952	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing ll" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 &S Ca -3 J-55 &-RT & regular cemen 3700' at 12:0 ely 24 hours b Amerada Pe By Position Assis Send	s OF THE COM t 9:15 AN, -RT SS Ceg. 8-RT Ceg. 5 Csg. New 5 Cs	12/29/31. New New Jel, 450 saci /51. Max pr- r casing shu poration r Operator	essur L-àff, 
3780' - Total Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 * 3767.59' Casing set at 3780' with 100 and 50 sacks Incer comput. 1300#. After W.O.C. for app JAN 3 1952 Approved except at follows:	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 &-RT S -3 J-55 &-RT S regular common 3700' at 12:0 ely 24 hours w Amerada Pe By Position Assis Send Name Amera	s OF THE COM t 9:15 AN, -RT SS Ceg. 8-RT Ceg. 5 Csg. New S Cs	12/29/31. New New New Jel, 450 sach /51. Max pro- r casing shut poration r operator et Superinter regarding well to m Corporation	ad est
3780' - Total Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 * 3767.59' Casing set at 3780' with 100 and 50 sacks Incer comput. 1300#. After W.O.C. for app JAN 3 1952 Approved except at follows:	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 SS Ca -3 J-55 R-3 &-RT S regular cemen 3700' at 12:0 ely 24 hours to Amerada Pe By Position Assis Send Name Amera	s OF THE COM t 9:15 AN, -RT SS Ceg. 8-RT Ceg. 5 Csg. New S Cs	12/29/31. Hew New New Jel, 450 sach /51. Max pro- r casing shur poration r operator et Superinte regarding well to	ad est
3780' - Total Depth - Lime. Finishe Ran 8-5/8" Cag. as follows: 6 Jts (245.48') 1 Jt (20.87') 34 Jts (1248.93 43 Jts (1781.19' 12 Jts ( <u>A89.12'</u> 96 * 3767.59' Casing set at 3780' with 100 and 50 sacks Incer comput. 1300#. After W.O.C. for app JAN 3 1952 Approved except at follows:	d drill: 32# J- 32# J- ) 32# J ) 24# J ) 32# B O sacks Plug to	ing 11" hole a 55 R-2 & R-3 & 55 R-2 Italian J-55 R-3 SS Ca -55 R-3 &-RT S -3 J-55 &-RT S regular common 3700' at 12:0 ely 24 hours w Amerada Pe By Position Assis Send Name Amera	s OF THE COM t 9:15 AN, -RT SS Ceg. 8-RT Ceg. 5 Csg. New S Cs	12/29/31. New New New Jel, 450 sach /51. Max pro- r casing shut poration r operator et Superinter regarding well to m Corporation	ad est

· · · · · ·

Contract Contract 

• •