

# DUPLICATE NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

SEP 24 1952

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

### Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

~~XXXXXX~~ September 23, 1952

Monument, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation**

**State BT<sup>MC</sup>**

(Company or Operator)

(Lease)

**Noble Drilling Corporation**

Well No. **5** in the **C/NE**  $\frac{1}{4}$  SW  $\frac{1}{4}$  of Sec. **35**

(Contractor)

T. **11-S**, R. **33-E**, NMPM, **Bagley-Pennsylvanian** Pool, **Lee** County.

The Dates of this work were as follows: **September 19, 1952**

Notice of intention to do the work ~~was~~ <sup>was not</sup> submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, and approval of the proposed plan ~~was~~ <sup>was not</sup> obtained.  
(Cross out incorrect words)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3768' - Total Depth - Line - Finished drilling 11" hole @ 2:30 PM, 9/17/52 - Ran a total of 120 Jts of 8-5/8" OD 32# Csg. set @ 3768' with 1500 sacks cement. Plug pumped to 3685' at 2:15 AM, 9/18/52 - Max pump pressure, 1200#. Ran Temperature survey, found top of cement outside 8-5/8" casing @ 1773', or, 40.2% fill. After WOC for 24 hours, tested 8-5/8" casing for 1/2 hour with 1100# - no pressure drop. Drilled cement from 3685' to 3768' and tested casing for 1/2 hour with 1100# - no pressure drop. Started drilling formation and 7-7/8" hole @ 6:30 PM, 9/19/52 -

Witnessed by **I. W. Wiseman** **Amerada Petroleum Corporation** **Forman**  
(Name) (Company) (Title)

Approved: **OIL CONSERVATION COMMISSION**

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **D. W. Tapp**

Position **Assistant District Superintendent**

Representing **Amerada Petroleum Corporation**

Address **Drawer D, Monument, New Mexico**

SEP 24 1952

(Title)

(Date)