

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

March 17, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Amerada Petroleum Corporation State BTD Well No. 2 in the C/NW/4 SE/4 of Sec. 35, T. 11-8, R. 33-E, N. M. P. M., Wilcat Field, Lea County.

The dates of this work were as follows: March 16 & 17, 1950

Notice of intention to do the work was ~~transmitted~~ submitted on Form C-102 on March 16, 1950 and approval of the proposed plan was ~~submitted~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,960' - Total Depth - Line. Ran Schlumberger Gamma Ray & Microlog surveys and Lane-Wells Electrical & Gamma Ray Surveys. Circulated & conditioned hole and ran 265 Joints of 5-1/2" O.D., 17#, 8-Md. Thd., Range 3, S. S. New Casing - Set at 10,960'. 24 - 5 1/2" Baker Centralizers from 10,945' to 8960' and 50 - 5 1/2" Weatherford Wall Scratchers from 10,945' to 10,675' and from 8960' to 9350'. Circulated & worked casing & cemented with 600 sacks of Trinity Slo-set cement, mixed 3% Jell and 1/4 of a pound of Slow Seal per sack. Plug pumped to 10875' at 1:45 A.M., 3-17-50. Maximum pump pressure 2300#.

Witnessed by C. E. Telge Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this

30 day of Mar. 1950

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Dr. T. J. [Signature]Position Assistant District SuperintendentRepresenting Amerada Petroleum Corporation
Company or OperatorMy commission expires 10-24-53Address Drawer D, Monument, New Mexico

Remarks:

Name

Title

