

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 8, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Amerada Petroleum Corporation State of **"D"** Well No. **3** in the
Company or Operator Lease
C/SR/4 SR/4 of Sec. **35**, T. **11-S**, R. **33-E**, N. M. P. M.,
Bagley-Siluro/Devonian Field **Lon** County.

The dates of this work were as follows: **September 7, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **September 3,** 19 **50**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,957' - Total Depth - Line. Run Temperature Survey - top of cement on outside of 5-1/2" casing at 7996', actual fill 3301', calculated fill 3780', ratio of actual to calculated fill 87%. Picked up 2-3/8" O.D. NBE tubing & 4-3/4" bit & checked top of cement at 10813'. Tested casing & connections with 1250' for 1/2 hour - no pressure drop. Drilled cement plug from 10813' to 10877' & washed to bottom to 10957'. Open hole from 10877' to 10957'. Continued with completion operations.

Witnessed by **E. V. Stephenson** **Amerada Petroleum Corporation** **Foreman**
Name Company Title

Subscribed and sworn before me this.....

I hereby swear or affirm that the information given above is true and correct.

11th day of **September**, 19 **50**Name **Doc Tapp**Position **Assistant District Superintendent**Representing **Amerada Petroleum Corporation**
Company or OperatorMy commission expires **10-24-53**Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

SEP 13 1950

Doc Tapp
Name
District Inspector
Title