

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	<b>X</b>

September 6, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
**Amerada Petroleum Corporation** State **MT "D"** Well No. **3** in the

Company or Operator **C/SR/4 SE/4** of Sec. **35**, T. **11-S**, R. **33-E**, N. M. P. M.,  
**Bagley-Silure/Devonian** Field **Lea** County.

The dates of this work were as follows: **September 4th & 5th, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **September 3,** 19 **50**  
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**10,957' - Total Depth - Line. Run Schlumberger's Electrical, Gamma Ray & Microlog Surveys. Run 268 Jts., 10,897', 5-1/2" O.D., 17#, 8-Md. Thi., Grade J-55 & 8640, Range 3, S. S. New Casing - Set at 10,897' & cemented with 600 Sacks of Long Horn Slo-set cement mixed 3/4 Jell & 1/2# flo-seal per sack. Plug to 10813' at 8:05 A.M., 9-5-50. Maximum pump pressure 2000#. Run 23 Baker Centralisers as follows - 8 spaced 30' apart from 10882' to 10672' and 15 spaced 30' apart from 9100' to 8680'. 50 Weatherford Scratchers through the above sections spaced 15' apart.**

Witnessed by **K. V. Stephenson** **Amerada Petroleum Corporation** Foreman  
Name Company Title

Subscribed and sworn before me this.....

**6th** day of **September**, 19 **50**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **R. L. Furze**

Position **Foreman**

Representing **Amerada Petroleum Corporation**  
Company or Operator

My commission expires **10-24-53**

Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

Date **SEP 8 - 1950**

**Roy Yarbrough**  
Name  
Oil & Gas Inspector  
Title