

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	<b>X</b>
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 21, 1955

Tatum, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation**  
(Company or Operator)

**State B.T. "D"**  
(Lease)

**Southwestern, Inc.** (Contractor), Well No. **5** in the **SW**  $\frac{1}{4}$  **SE**  $\frac{1}{4}$  of Sec. **35**

**T11-S**, R. **33-E**, NMPM., **BAGLEY- PENNSYLVANIA** Pool, **Lea** County.

The Dates of this work were as follows: **5-11-55 to 6-13-55**

Notice of intention to do the work (was) (~~was not~~) submitted on Form C-102 on **5-9-55**, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**9450' TD 9020' DOD Line - Ran Halliburton Cement Retainer and set @ 8969' and diesel oil/cement squeezed perforation in  $\frac{5}{8}$ " casing (9016' to 9055') with 100 sacks regular cement and 10 bbls kerosene - squeezed  $31\frac{1}{2}$  sacks cement into formation - could not release Halliburton Retrievable Cement Tool. Ran HOMO string shot and backed tubing off from Halliburton Retrievable Cement Tool. Ran HOMO fishing tools attempting to recover Cement Tool. Ran wash-over pipe and milling tools - recovered fish. Drilled out cement from 8982' to 9043' and swabbed perforations (9016' to 9043') for  $14\frac{1}{2}$  hrs - recovered part of tubing lead oil - lacked 12 barrels for complete recovery - acidized perforations (9016' to 9043') with 500 gallons retarded acid. Swabbed perforations for  $18\frac{1}{2}$  hrs and recovered lead oil plus 249 bbls formation water. Ran Baker Retainer and squeezed perforations (9016' to 9042') with 100 sack cement.**

Witnessed by **I. W. Wiseman** (Name) **Amerada Petroleum Corporation** (Company) **Foreman** (Title)

Approved: **OIL CONSERVATION COMMISSION**

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **[Signature]**

Position **Assistant District Superintendent**

Representing **Amerada Petroleum Corporation**

Address **Roswell Star Route Tatum, N.M.**

(Title)

(Date)