

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-163
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-01025
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B9950
7. Lease Name or Unit Agreement Name STATE BTA
8. Well No. 1
9. Pool name or Wildcat BAGLEY SILURO DEVONIAN

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator AMERADA HESS CORPORATION	
3. Address of Operator DRAWER D, MONUMENT, NEW MEXICO 88265	
4. Well Location Unit Letter <u>J</u> : <u>1980</u> Feet From The <u>SOUTH</u> Line and <u>1980</u> Feet From The <u>EAST</u> Line Section <u>2</u> Township <u>12S</u> Range <u>33E</u> NMPM LEA County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4224' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: CEMENT SQUEEZE ☒	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PLAN TO MIRU PULLING UNIT & TOH W/RODS & PUMP. INSTALL BOP & TOH W/TBG. TIH W/4-3/4" BIT TO 10,800' & TOH. TIH W/5-1/2" RBP & PKR. SET RBP AT ±9620' & TEST TO 3000#. SPOT 3 SKS. SAND ON RBP. LOAD CASING & PRESS. TEST TO 1000#. IF CSG. DOES NOT HOLD, LOCATE CSG. LEAK & CEMENT SQUEEZE AS DETERMINED BY INJ. TEST. DRILL OUT RETAINER & TEST SQUEEZE CIRC. SAND OFF RBP, RELEASE PLUG & TOH. TIH W/PKR. SET AT ±10,700', TEST TBG. TO 3500# & CSG. TO 500#. ACIDIZE DEVONIAN ZONE 5-1/2" CSG. PERF. FR. 10,752'-10,775' W/2000 GALS. 15% NEFE HCL ACID. SWAB LOAD & EVALUATE PRODUCTION POTENTIAL.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. L. Wheeler, Jr. TITLE SUPV. ADM. SVC. DATE 5/10/91
TYPE OR PRINT NAME R. L. WHEELER, JR. TELEPHONE NO. 393-2144

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE MAY 13 1991
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 10 1991

OFFICE
HOURS OFFICE