NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	<u> </u>		<u> </u>		<u> </u>	
OTICE OF INTENTION CHANGE PLANS		Notice of Intention to Temporarily Abandon W	ELL	Notice of Intention to Drill Deeper		
otice of Intention Drug Well		Notice of Intention to Plug Back		Notice of Intention to Set Liner		
otice of Intention Squeeze	x	Notice of Intention to Acidize		Notice of Intention to Shoot (Nitro)		
otice of Intention Gun Perforate		Notice of Intention (Other)		Notice of Intention (Other)		
OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO		Tatum, New Mexico		<i>J</i> uly 25, 19 59		
		o certain work as described b				····
Amerada Petroleum (nAu	.Well No	in	
SE 1/4 of	Sec) T 12-8	33-E NMPM.,	Bagley Silure	Devonian	Po
(40-acre Subdivision)	_					
otal Depth 11,766' 0,865' to 10,895' 8	Plugged	Back Bepth 10,940 to 10,934.			ferations	
0,865! to 10,895! 4 NTEMSIONS ARE: Run rom 10,912' to 10,9	Plugged 10,912' Cast Iro	Back Bepth 10,940 to 10,934'. In Retainer & Set @ Sz. 81e-Set Comm	10,906' & So	-1/2" Casing per queese Bettom 5-: Valves & Put Wei	1/2" Caming	pez
O,865' to 10,895' & WINNSIONS ARE: Run rom 10,912' to 10,9 reduction from Pres	Plugged k 10,912' Cast Iro 34' W/73 sent tep	Back Bepth 10,940 to 10,934°. In Retainer & Set @ Sz. Sle-Set Comm 5-1/2" Gasing perf	10,906' & So t. Run Flow from 10,86	1/2" Casing periods of the logo of the log	1/2" Casing 11 back on	pez
O,865' to 10,895' & WYRNSICHS ARE: Run From 10,912' to 10,9 Production from Pros	Plugged k 10,912' Cast Iro 34' W/73 sent tep	Back Bepth 10,940 to 10,934°. In Retainer & Set @ Sz. Sle-Set Comm 5-1/2" Gasing perf	10,906' & So t. Run Flow from 10,86	-1/2" Gasing per queese Bettom 5-: Valves & Put Wei " to 10,895".	1/2" Casing 11 back on	pez
Approved Approved Approved	Plugged 10,912' Cast Ire 34' W/73 sent top	Back Bepth 10,940 to 10,934. In Retainer & Set @ Sz. Sle-Set Comm 5-1/2" Casing perf.	Ampada Pei	1/2" Casing periods of the logo of the log	1/2" Casing 11 back on ion	pez
Approved Except as follows:	Plugged 10,912' Cast Ire 34' W/73 sent top	Back Bepth 10,940 to 10,934. In Retainer & Set @ Sz. Sle-Set Comm 5-1/2" Casing perf.	Ampada Pet Ampada Pet Ampada Pet Ampada Pet	Talves & Put West' to 10,895'. Sompany or Operator (t District Super	1/2" Casing 11 back on ion rintendent g well to:	pez

Tatum, New Mexico