

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back Well	X

July 19, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State HTA Well No. 1 in the

Company or Operator

Lease

NW 1/4 Sec. 2 of Sec. 2, T. 123, R. 33E, N. M. P. M.,
Wildcat Field, Lea County.

The dates of this work were as follows: July 12, to 19, 1949

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on July 11, 1949
and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11766' T.D. Chert, 10990' PBD. Ran cement plug from 11766 to 11453' W/35 sx. cement. Set Baker Model K, C.J. Retainer @ 11155', squeezed W/150 sx. cement. Drilled out to 11030' & perf. 5 1/2" from 11000' to 11015' W/60 shots, Made D.S.T. Results Unsatisfactor Set Baker Model K. Retainer @ 10990! Squeezed perf. from 11000 to 11015' W/35 sx. cement. Perf. Csg. from 10950 to 10965' W/60 shots. Acidized W/250 gals. Dowell XF-18 acid. Tested 4 1/2 hrs. on 1/2" choke, made 400.20 bbls. oil, Gas Vol. 49,385 cu. ft. per day, GOR 23, Gravity 44.4 Corrected. Well Completed.

Witnessed by K.V. Stephenson Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

19th day of July 1949

Name _____

Will Hails Taylor
Notary Public

Position Asst. Dist. Supt.,

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires MY COMMISSION EXPIRES MARCH 29, 1952

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED
JUL 22 1949

Reg. [Signature]
Name
Title