


**OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELLS**



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |  |  |          |
|--|--|--|----------|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |  | REPORT ON REPAIRING WELL                       |          |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |  | REPORT ON PULLING OR OTHERWISE ALTERING CASING |          |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                |  | REPORT ON DEEPENING WELL                       |          |
| REPORT ON RESULT OF PLUGGING OF WELL                       |  | Report on Setting Casing                       | <b>X</b> |

December 14, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation State ETA Well No. 1 in the \_\_\_\_\_  
Company or Operator Lease  
NW 1 SE 1 of Sec. 2, T. 12S, R. 33E, N. M. P. M.,  
Wildcat Field, Lea County.

The dates of this work were as follows: December 14, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on December 13, 1948  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

3930' Total Depth, Line. Ran Schlumberger Electric Survey & Gamma Ray. Rigged up and ran 128 joints of 8-5/8" O.D. 32#, R-2, 8Rd. Thd. J-55, S.S. Casing (New) and set at 3929' and cemented with 1400 sacks Bulk cement & 100 sacks Incor(900 sx. Longhorn Slow set & 500 Sx. Reg. Bulk cement, 1000 sx. mixed 3% Howcogel. Plug pumped to 3875' at 4:15 A.M. 12-15-48 with final pressure of 1200#

Witnessed by E.E. Shirley Amerada Petroleum Corporation Farm Boss  
Name Company Title

Subscribed and sworn before me this 15th day of December 1948  
Will Hails Taylor  
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name Don Topp  
Position Asst. Dist. Supt.  
Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires \_\_\_\_\_

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Roy Garbrough  
Name  
Oil Conservation Commission  
Title