

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B9950

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State BT"A"
3. Address of Operator 1209 South Main, Lovington, New Mexico	9. Well No. 2
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>12-S</u> RANGE <u>33-E</u> NMPM.	10. Field and Pool, or Wildcat Bagley-Pennsylvanian
15. Elevation (Show whether DF, RT, GR, etc.) 4249' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

State BT"A" #2 - Cast Iron Retainer @ 7325' & Squeezed 5-1/2" Csg. w/100 Sk. & 1800# Pump Pressure. Spot 5 Sk. on top of Retainer. Cut 5-1/2" Csg. @ 4500', spot 30 Sk. plug @ 4520' to 4394', 30 sk. plug 3750' - 3876'. Spot 10 sk. plug in top of 7-5/8" with Dry Hole Marker.
11-3/4" Csg. @ 316' Cement Circulated
7-5/8" Csg. @ 3790' Cement Circulated
5-1/2" Csg. @ 9100' top of cement @ 5298'

Amerada Hess expects to start this work on 1-29-73

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Hambleton TITLE Area Superintendent DATE 1-11-73
SIGNED BY Joe D. Ramey
Dist. I, Supv.
APPROVED BY _____ TITLE _____ DATE JAN 15 1973

19. SIGNATURES OF APPROVAL, IF ANY: