

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	<b>X</b>

November 30, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

**Amerada Petroleum Corporation** State **BT "I"** Well No. **1** in the  
Company or Operator Lease  
**C/M/4 M/4** of Sec. **2**, T. **12-S**, R. **33-E**, N. M. P. M.,  
**Bagley-Siluro/Devonian** Field **Lee** County.

The dates of this work were as follows: **November 29, 1950**

Notice of intention to do the work was ~~XXXXXXXX~~ submitted on Form C-102 on **November 28,** 19 **50**  
and approval of the proposed plan was ~~XXXXXXXX~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**10,960' - Total Depth - Line. Ran Schlumberger Electrical, Gamma Ray & Microlog Surveys. Ran 270 Jts., 10,912', 5-1/2" O.D., 17#, 8-Rd. Thd., Grade J-55 & 8640, Range 3, S.S. New Casing - Set at 10,922' & cemented with 600 sacks of Trinity Silo-Set cement, mixed 3% Jell & 1/4# Flow-seal per sack. Plug to 10,836' at 7:30 A.M., 11-29-50. Maximum pump pressure 1400#. Ran 20 Baker Centralizers spaced 30' apart from 8850' to 10907' and 43 Weatherford Scratchers spaced 15' apart through the above sections.**

Witnessed by **C. E. Tolge** **Amerada Petroleum Corporation** **Farm Boss**  
Name Company Title

Subscribed and sworn before me this.....

I hereby swear or affirm that the information given above is true and correct.

**1st** day of **December**, 19 **50**Name **Dw. Tapp**Position **Assistant District Superintendent**Representing **Amerada Petroleum Corporation**  
Company or OperatorMy commission expires **10-11-54**Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED  
DEC - 4 1950  
Date

**Oil & Gas Inspector**  
Name  
Title