

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

RECEIVED

AUG 28 1950

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

August 24, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation State BT #1 Well No. 1 in the  
Company or Operator  
C/HW/4 HW/4 of Sec. 2, T. 12-S, R. 33-E, N. M. P. M.,  
Bagley-Siluro/Devonian Field Lea County.

The dates of this work were as follows: August 23, 1950

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on August 23, 1950  
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3833' - Total Depth - Line. Ran Schlumberger Electrical & Gamma Ray Surveys. Ran 99 Jts. of 3-5/8" O.D., 32#, 8-Rd. Thd., Grade J-55, Range 2 & Range 3, New & SH S.S. Casing - Set at 3833' and cemented with 1000 Sacks Long Horn Regular cement, mixed with 3% Jell, 450 sacks Lone Star Regular cement and 50 sacks of Incon Cement - Total of 1500 sacks. Plug to 3761' at 10:45 P.M., August 23, 1950. Maximum pump pressure 1200#.

Witnessed by C. E. Nichols Amerada Petroleum Corporation Farm Bureau  
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

24th day of August, 1950

Name *Dw. Tapp*

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires 10-24-53

Address Drawer D, Monument, New Mexico

Remarks:

*K. S. Blum*  
Name  
Engineer District I  
Title