

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

RECEIVED

AUG 28 1950

OIL CONSERVATION COMMISSION
HOSES-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

August 26, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation State **BT #1** Well No. **1** in the _____
 Company or Operator Lease
G/M/4 M/4 of Sec. **2**, T. **12-S**, R. **33-E**, N. M. P. M.,
Bagley-Silure/Devonian Field **Lee** County.

The dates of this work were as follows: **August 25, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **August 23,** 19**50**
 and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3833' - Total Depth - Line. Temperature Survey - Top of cement on outside of 8-5/8" casing 714', per cent fill 66.5. Checked top of cement at 3761' and tested 8-5/8" casing & connections with 1200# for 1/2 hour - no pressure drop. Drilled cement from 3761' to 3833' and tested casing & connections with 1200# for 1/2 hour - no pressure drop. Started drilling formation and 7-7/8" hole at 11:45 A.M., August 25, 1950.

Witnessed by **C. E. Nichols** **Amerada Petroleum Corporation** **Farm Boss**
 Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

26th day of **August**, 19**50**

Name **Don Tipp**Position **Assistant District Superintendent**

Representing **Amerada Petroleum Corporation**
 Company or Operator

My commission expires **10-24-53**

Address **Drawer D, Monument, New Mexico**

Remarks:

R. S. Blum
 Name
Engineer District 1
 Title