

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

AUG 25 1950

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	<b>X</b>

August 16, 1950

Mammoth, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

**Amerada Petroleum Corporation** State **NY "I"** Well No. **1** in the  
Company or Operator Lease  
**C/M/4 NW/4** of Sec. **2**, T. **12-S**, R. **33-E**, N. M. P. M.,  
**Bagley-Siluro/Denverian** Field **Lee** County.

The dates of this work were as follows: **August 15, 1950**

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on **August 15, 1950** 19  
and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**307' - Total Depth - Red Bed. Ran 7 Joints of 13-3/8" O.D., 36#, Armo Spiral Weld, Slip Joint New Casing, set at 297' and cemented with 175 sacks of Trinity Regular cement & 50 sacks of Trinity High-Early cement. Plug to 282' at 6:00 P.M., 8-15-50. Maximum pump pressure 200#. Cement Circulated.**

Witnessed by **C. E. Nichols** **Amerada Petroleum Corporation** **Farm Boss**  
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

**17th** day of **August**, 19 **50**

Name **Ben T. [Signature]**  
Position **Assistant District Superintendent**  
**Amerada Petroleum Corporation**

Notary Public

Representing **Amerada Petroleum Corporation**  
Company or Operator

My commission expires **10-24-53**Address **Drawer B, Mammoth, New Mexico**

Remarks:

**APPROVED****DATE AUG 25-1950****Oil & Gas Inspector**

Name

Title