

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
JUN 26 1951  
OIL CONSERVATION COMMISSION  
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

|  |  |  |   |
|--|--|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS                    |  | REPORT ON REPAIRING WELL                       |   |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL |  | REPORT ON PULLING OR OTHERWISE ALTERING CASING |   |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                |  | REPORT ON DEEPENING WELL                       |   |
| REPORT ON RESULT OF PLUGGING OF WELL                       |  | REPORT ON SETTING CASING                       | X |

June 23, 1951

Monument, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

State BT "D"

Well No. 4

in the

Company or Operator

Lease

SE/4 SW/4

of Sec. 2

T. 12-S

R. 33-E

N. M. P. M.,

Bagley-Pennsylvanian

Pool

Lee

County.

The dates of this work were as follows: June 21, 1951

Notice of intention to do the work was (witness submitted on Form C-102 on June 21, 1951 and approval of the proposed plan was (witness obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3825' - Total Depth - Line. Ran 88 Jts. 8-5/8" O.D., 32#, Grade J-55, Range 3, S.S. New Casing & 5 Jts., 8-5/8" O.D., 28#, Grade H-40, S-Md. Thd., Range 3, S.S. New Casing, set at 3825' and cemented with 1000 sacks Regular cement, mixed with 3% Jell, 450 sacks Regular cement & 50 sacks Incer cement - total of 1500 sacks. Plug to 3739' at 9:00 P.M., 6-21-51. Maximum pump pressure 1100#.

Witnessed by E. V. Stephenson

Name

Amerada Petroleum Corporation

Company

Foreman

Title

APPROVED:

OIL CONSERVATION COMMISSION

*Ray Yackbrough*  
Name  
Oil & Gas Inspector  
JUN 26 1951  
Title

Date

19

I hereby swear or affirm that the information given above is true and correct.

Name

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation

Company or Operator

Address Drawer D, Monument, New Mexico



1911

1911

1911

1911