

DUPLICATE

## NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent. The work specified is to begin. A copy will be returned to the sender on which will be given the approval, with modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

|   |                                     |   |
|---|-------------------------------------|---|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL |
| NOTICE OF INTENTION TO CHANGE PLANS         | <input type="checkbox"/>            | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING |
| NOTICE OF INTENTION TO REPAIR WELL          | <input type="checkbox"/>            | NOTICE OF INTENTION TO PLUG WELL                      |
| NOTICE OF INTENTION TO DEEPEN WELL          | <input type="checkbox"/>            |   |

Monument, New Mexico

August 28, 1951

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to do certain work as described below at the.....

Amerada Petroleum Corporation

State of N.M.

Well No. 2

C/NR/4 SW/4

Company or Operator

2

12-S

Lease

33-E

Bagley-Pennsylvanian

of Sec.

Lea

T.

R.

N. M. P. M.

Field.

County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

3795' - Total Depth - Line. Finished drilling 11" hole at 10:15 PM, 8/26/51.  
Ran 8-5/8" Casing as follows:

|   |          |
|---|----------|
| 1 Jt 8-5/8" OD 36# N-80 R-3 X-Line Csg. New     | 34.98'   |
| 13 Jt 8-5/8" OD 40# N-80 R-2 X-Line Csg. New    | 397.79'  |
| 15 Jt 8-5/8" OD 40# N-80 R-3 X-Line Csg. New    | 583.44'  |
| 27 Jt 8-5/8" OD 36# N-80 R-3 8-RT Csg. New      | 1057.49' |
| 6 Jt 8-5/8" OD 36# J-55 R-2 8-RT Csg. New       | 193.57'  |
| 36 Jt 8-5/8" OD 32# J-55 R-3 8-RT Csg. LT&C New | 1473.89' |
| 1 Jt 8-5/8" OD 36# J-55 R-3 8-RT Csg. LT&C New  | 39.10'   |

A total of 99 Jts for 3780'.26'. Casing set at 3795' and cemented with 1450 sacks regular of which 1000 sax were mixed with 3% Jel, and 50 sacks Inco cement - Total of 1500 sacks. Plug to 3727' at 11:50 AM 8/27/51. Max. pump pressure, 800#. After W.O.C. approx. 24 hours, will test for casing shut-off.

Approved....., 19.....  
except at follows: AUG 30 1951

Amerada Petroleum Corporation

Company or Operator

By

Assistant District Superintendent

Position

Send communications regarding well to

Name

Amerada Petroleum Corporation

Address

Drawer D, Monument, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

Oil &amp; Gas Inspector