NEW MEXICO OIL CONSERVATION COMPISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent begin. A copy will be returned to the sender on which will be given the approximately approximat the work specified is to indiffications considered the simple followed, advisable, or the rejection by the Commission or agent, of the plan submitted. The plan and work should not begin until approval is obtained. See additional instructions in

		inaic	sate nature		e by checking belov			
OTICE OF SHUT-OF		TO TEST CASI	NG	X	NOTICE OF INT	ENTION TO SI		
OTICE OF	INTENTION	TO CHANGE P	LANS		NOTICE OF INT	ENTION TO P		
OTICE OF	INTENTION	TO REPAIR W	ELL		NOTICE OF INT	ENTION TO P	LUG WEL	L
OTICE OF	INTENTION	TO DEEPEN W	VELL					
			Mon	ument	New Mexico	Aug	ust 25,	1951
					Place		Date	***************************************
IL CONSER anta Fe, Nev	VATION CO	MMISSION,						
entlemen:								
	a notice of i	ntention to do cer	rtain work	as desci	ribed below at the			
		Corporation		BT "I	,n		1	in C/SE/4 S
			Lease					
				, N	. м. р. м.,Bagley	-311mro/Den	ronian	Field
L	4		County.					
		FULL DET	AILS OF	PROP	OSED PLAN O	F WORK		
n.	otal Dept an Schlum	h - Lime. F	inished	drill	nd regulation ing 6–3/4" ho a Ray & Micro	le at 8:30	AM, 8/2	2/51 .
ni Co Se 2/ ar al	otal Dept an Schlum ts 5½ 0D emented w eal per s 500#. Ra nd 10835	h - Lime. Faberger's Ele Grade J-55 with 600 sack ack. Plug to 11 Baker 0 to 10955's	inished ectrical, & 8640, as slo-se to 10880 entralia	drill, Gamm 8-RT st cem at 8 zers s		le at 8:30 log Surveys ew - Set at n 3% Jel an 51. Max. Pu rt from 900	AM, 8/2: 109701 11/4#: 109701 109701 109701 109701	2/51. 269 and fle- sure, 060'
pproved	otal Dept an Schlum ts 5½ OD emented weal per s 500#. Ra nd 10835 bove sect	h - Lime. Faberger's Ele Grade J-55 with 600 sack ack. Plug to 11 Baker 0 to 10955's	inished etrical, & 8640, as alo-se to 10880; entralise and 22 We W.O.C.	drill , Gamm 8-RT st cem t at 8 zers seather for a	ing 6-3/4" home Ray & Microl R-3 SS C g. No meta mixed with 3:30 PM, 8/24/2 paced 30' apart ford Scratches approximately to	le at 8:30 log Surveys ew - Set at h 3% Jel an 51. Max. Pu rt from 900 rs spaced 1 we will tes	AM, 8/2: 10970! ad 1/4#: imp pression to 90: 5! aparent casing	2/51. 269 and fle- sure, 060° t in g shut-
pproved	otal Dept an Schlum ts 5½ OD emented weal per s 500#. Ra nd 10835 bove sect	h - Lime. Faberger's Electric Grade J-55 with 600 sack ack. Plug to 11 Baker 0 to 10955' a ions. After	inished etrical, & 8640, as alo-se to 10880; entralise and 22 We W.O.C.	drill , Gamm 8-RT st cem t at 8 zers seather for a	ing 6-3/4" home Ray & Microl R-3 SS C g. No meta mixed with 3:30 PM, 8/24/2 paced 30' apart ford Scratches approximately to	le at 8:30 log Surveys ew - Set at h 3% Jel an h 1. Max. Pu rt from 900 rs spaced 1 we will tes Patroleum Company	AM, 8/2. Ran 109701 Id 1/4# Imp pres 10: to 9 15: apare 15: apare 15: apare 16: casing	2/51. 269 and fle- sure, 060° t in g shut-
pprovedxxcept at follo	otal Dept an Schlum ts 5½ 0 D cmented w eal per s 500#. Ra nd 10835 bove sect ff.	h - Lime. Faberger's Electric Grade J-55 with 600 sack ack. Plug to 11 Baker 0 to 10955' a ions. After	finished ectrical, & 8640, as slo-se to 10880; entralise and 22 We W.O.C.	drill , Gamm 8-RT st cem t at 8 zers seather for a	ing 6-3/4" hois Ray & Microl R-3 SS C g. Noteth mixed with 130 PM, 8/24/2 apaced 30' apaced 30' apaced ford Scratched approximately to a second secon	le at 8:30 log Surveys ew - Set at n 3% Jel an 51. Max. Pu rt from 900 rs spaced 1 we will tes Petroleum Company Company istant Dist communication	AM, 8/2 Ran 109701 ad 1/4# Imp pres 00 to 9 5 apar at casing	2/51. 269 and fle- sure, 060° t in g shut-
al pprovedxxcept at follo	otal Dept an Schlum ts 5½ 0 D cmented w eal per s 500#. Ra nd 10835 bove sect ff.	h - Lime. Faberger's Elector of the 600 sack ack. Plug to 10955' ack ack. After	finished ectrical, & 8640, as slo-se to 10880; entralise and 22 We W.O.C.	drill , Gamm 8-RT st cem t at 8 zers seather for a	ing 6-3/4" hona Ray & Micro R-3 SS C g. No eth mixed with 30 PM, 8/24/2 paced 30' apar ford Scratcher pproximately to Amerada By Position Assi Send	le at 8:30 log Surveys ew - Set at h 3% Jel an 51. Max. Pu rt from 900 rs spaced 1 we will tes Petroleum Company Company istant Dist communication ida Petrole	AM, 8/2 Ran 109701 ad 1/4 Imp pres 00 to 9 5 apar t casing rict Superior prict Superior prict Superior casing	2/51. 269 and fle- sure, 060° t in g shut- cerintende g well to