## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

40. SF COPIES SCEEIVES	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

CONDITIONS OF APPROVAL, IF ANY:

## OIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 -

FILE	FE		SANT	A FE, NEW	MEXICO 8	7501		KEALZEG	19-1-
U.S.G.	s						5a. Indicate Typ	e of Lease	
<b>}</b>	OFFICE						State X	Fe	•
OPER	ATOR						5. State Oil & G NM 211	ds Ledse No.	
100	MAT HEE THIS FORM :	FOR BRODOSA	OTICES AND R	EPORTS ON	ACK TO A DIFFERE	NT RESERVOIR.			
OIL WELL	X SAS [		OTHER-				7. Unit Agreeme	nt Name	
2. Name of Operator  Sun Exploration and Production Company						8. Form of Lease Name State C A/C 1			
P. O. Box 1861, Midland, TX 79702							9. Well No.		
4. Location of Well  M 660 South 660  UNIT LETTER							10. Field and Pool, or Wildcat Bagley Penn		
THE			2						III
	~~~~~~						VIIIIII	7777777	777.
			15. Elevation 4237 GR	n (Show whether	DF, RT, GR, etc	.) 	12. County Lea		
16.			ropriate Box T NTION TO:	o Indicate N	ature of Noti	ce, Report or Ot subsequen	her Data T REPORT OF	:	
PERFORM PENTEMPORARILY PULL OR ALTE	ABANDON		PLUG AM Change	PLANS	REMEDIAL WORK COMMENCE DRIL CASING TEST AN OTHER Clea	LING OPNS.	PLUG	RING CASING AND ABANDONMI	_
17. Describe	Proposed or Compi	eted Operati	ons (Clearly state	all pertinent deta	iiis, and give per	tinent dates, including	estimated date of	starting any p	ropos
	MIRU Otis V	√L. Tag	; fill in tbg	g via WL at	t ± 10716.	RD Otis, SDF	N.		
7/18/85			IU BOP. RU ( latch Pkr.		erf 3-1/2"	P.C. tbg at ±	10690. R1:	se pkr.	РОН
7/ <b>2</b> 0/85	RIH w/5-7/8	3" bit 8	11 DCs on 2	2-7/8 WS.	Tag fill a	t ± 11222. S	DFN.		
7/22/85	MIRU AA WS. Load hole w/prod wtr. Broke circ & wash fill from 11220 to 11255. Fill became solid — could not wash down. Raise bit to $\pm$ 10,000. SDFN.								
7/23/85	Lower bit & tag fill at $^\pm$ 11255. MIRU Star Tool reverse rig. Load hole & break circulation. CO to <b>PB</b> TD 11275. Losing 3 BPM. Circ hole cln. Raise bit to $^\pm$ 10000. Close BOP. EIR down 7" casing annulus @ 4 BPM, 50 PSIG. SDFN.								
						7/8" WS & bit.	*********		
	pkr at ± 10 Put on inje	0723. Fection (	Rise overshoth 7:00 P.M.	t. Circ pl Inj. rate	kr fluid. 4000 BWPD	profile on 3- Latch oversho at 0 PSI T.P.	t. ND ROP.	NW WH.	
18. I hereby c	ertify that the infor	macion abov	e is true and compl	ete to the best o	i my knowledge s	and belief.	O.G.	VAC	
SICHED	Du Hm	Lond	2	TITLES	r. Acctg. <i>I</i>	Asst.	MIDLAND, TE		
APPROVED	ORIGINAL SIG!	NED BY JE					AUG	G 2 3 198	<del></del>

RECEIVED

AUG 22 1985

OACO. Hobbe conce